

→ 4002 CENTRALIZED OFFICE SHREDDER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | wide, 16" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs | lifetime warranty on the cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy "twin drive system" with dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 44 gallon shred volume

Dimensions (D x W x H): 23 % x 25 % x 38 % inches, Shipping weight: 239 lbs. (strip-cut) / 240 lbs. (cross-cut).









EASY SWITCH



Oversized, multifunction control element uses integrated optics to indicate operational status.

CONVENIENT SHRED BIN



A large capacity shred bin makes bags optional.

→ 4002 STRIP-CUT

Strin width

July Midul	1/4
·	(6 mm
Sheet capacity	32-35
Security level	2
Feed opening	16''
Max horsenower	1 3/4

→ 4002 CROSS-CUT

1 7 4002 01000-001		
Particle size	3/16" x 1 ½" (4 x 40 mm)	
Sheet capacity	24-26*	
Security level	3	
Feed opening	16"	
May horeanowar	1 3/,	

max. norsepower	1 %	
→ 4002 CROSS-CUT		
Particle size	3/32" x 5/8" (2 x 15 mm)	
Sheet capacity	14-16*	
Security level	4	
Feed opening	16"	
Max. horsepower	1 3/4	

^{*} may vary due to variations in paper and power supply



CUL) US