

# Alum-Kleen

*Concentrated and Soluble Powder*

Designed to function most efficiently at elevated temperatures. Cleans and strips away oil, grease and other deposits from transmissions, radiators, and other metal parts without foaming problems. It will not leave a film or residue on parts and it will not plug up spray cabinets' jets, or build-up inside the spray cabinet.

## Use On

- Transmissions
- Engines
- Radiators
- Metal Parts

## Effective Against

- Grease
- Oils
- Deposits

## Features and Benefits

- Generates less waste than solvent cleaning
- Contains rust inhibitors to prevent flash rusting
- Effectively inhibits the growth of mold and mildew and the odors caused by them.

## Properties

Appearance	White Powder
Fragrance	Chlorine
Flash Point	None
VOC Content	< 2.0% by wt.
Solubility	Complete in water

## Directions *Complete directions on product label*

**For Spray Cabinets:** Dilute 1-2 ounces per gallon of water. Maintain temperature at 190°F for best results.

**For Dip Tanks:** Dilute 1 ounce per gallon of water. Let parts soak for 15-20 minutes and then rinse.

## Ingredients

Sodium Carbonate  
Sodium Sulfate  
Water  
Sodium Borate  
Sodium Orthosilicate

## CAS Number

497-19-8  
7757-82-6  
7732-18-5  
1303-96-4  
1344-09-8

## Safety

DANGER: Causes serious eye irritation. May damage fertility or the unborn child.

## DOT Shipping (Ground Transportation)

Proper Shipping Name	None
Class	None
ID Number	None
Packing Group	None

## Quantities

100 pounds  
50 pounds  
25 pounds

## NFPA® RATINGS

