

DESCRIPTION

This product is an emulsion based road sealer designed to beautify and protect your roads. This product is rubberized, fills alligator cracks and provides traction.

PRECAUTIONS: Avoid applying sealer when rainfall is likely. Avoid applying sealer when temperatures drop below 55°F. Allow all repaired surfaces to cure prior to sealing. If the crack filler is firm you may seal over. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

CAUTION – HARMFUL OR FATAL IF SWALLOWED.

Keep container capped when not in use. Non-flammable.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

FIRST AID:

EYES: Gently flush with large amounts water for at least 15 minutes. If symptom persists consult a physician.

INHALATION: Remove to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial resuscitation. **IMMEDIATELY CALL A PHYSICIAN.**

SKIN: Wash area with soap and water.

INGESTION: Do not induce vomiting.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not store in unmarked containers. Rinse empty container before disposal.

EZ SEAL

Sand Mix Asphalt Sealer

- 2 year warranty
- Rubberized formula
- Fills alligator cracks
- Non skid formula, Low VOC formula

KEEP OUT OF REACH OF CHILDREN

CAUTION

HARMFUL OR FATAL IF SWALLOWED.

May irritate eyes and skin.

See side panel for additional precautions.

Reorder From:

 **Goldstar Products Inc.**
P.O. BOX 291630 • DAVIE, FL 33329
1-800-239-5699
Tax ID # 65-0597470

DIRECTIONS

COVERAGE: Coverage rates vary depending upon the condition of the existing blacktop. Smooth & previously sealed roads will average 400-500 square feet per pail. Rough and unsealed surfaces will average 300-400 sq. ft. per pail. Rough / road-grade asphalts with larger aggregate can cause lower than normal coverage rates. A thick coat is recommended as thin coats will result in uneven coverage.

PREPARATION: Sweep and clean off entire road. If pavement is extremely hot, apply a fine water mist prior to sealing; brush out any remaining puddles. You can edge the road with a large paint or wall paper brush by dipping brush into sealer and slowly edging the road. Newly paved surfaces must cure for a minimum of 12 months before sealing.

APPLICATION: DO NOT DILUTE SEALER. Apply sealer only when ground temperature is 55°F and rising and rain is not likely. Early spring or late fall application when sun is at a low angle can prevent sealer from curing properly which may cause tracking. Complete surface preparations and allow area to completely dry. Thoroughly mix all pails of this product. Pour across the high end of the road in a ribbon pattern. Spread sealer side to side by pulling the squeegee across the road removing the excess sealer. Remember to apply firm/steady down pressure as you want to leave a thick coat. Thick coats are better than one thin coat. If needed, allow first coat to dry thoroughly before applying the second coat.

CLEAN UP & STORAGE: While wet, clean up with soap and water. If dry, scrub with citrus based cleaner. Containers are recyclable. Do not heat or store container in temperatures above 110°F. **KEEP FROM FREEZING!** Product is Non-Hazardous.

This Product Contains/CAS Number:

Crystalline Silica/14808-60-7;
Carbon Black/1333-86-4;
Petroleum Asphalt/8052-42-4;
Polymer/Proprietary.