



## DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways.

Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear eye protection, protective clothing, protective gloves.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. **IF**

**ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

**⚠ WARNING:** This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**DISPOSAL:** Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*



**NO-STICK**

## Protect Metal Surfaces

- REDUCES FRICTION FOR MORE EFFECTIVE PLOWING
- WILL NOT WASH OFF

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:** One Gallon (128 fl. oz.)

## DESCRIPTION

This snow plow coating deposits a hard, slippery layer of silicone on plow blades and other snow removal equipment. Snow slides off treated surfaces easier and faster, allowing more snow to be moved with less fuel and less wear on equipment. In addition, the impervious silicone layer protects metal surfaces both in use and in storage.

## DIRECTIONS

Apply coating to plow blades and other exposed metal and painted surfaces by spraying, brushing or rolling.

Equipment may be used immediately after application, but best results are obtained when coating is allowed to dry for 30 minutes.

For maximum protection, apply coating at the end of each work period. Several applications over the summer storage periods will preserve equipment.

This snow plow coating is ideal for use on shovels, loaders, snow throwers and truck beds to help

## NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

## CONTAINS/CAS NUMBER:

Distillates (Petroleum), Hydrotreated Light/64742-47-8; Polydimethylsiloxane/63148-62-9; Toluene/108-88-3; Benzene/71-43-2; Cumene/98-82-8

Please Recycle.

0385.032118