Sewer digestant with enzymes

This product utilizes the powerful waste digesting abilities of natural enzymes and bacteria. It is a blend of special bacteria strains (both anaerobic and aerobic types) cultured for their ability to digest and liquefy organic sewage - quickly, efficiently and without odors! These potent bacteria are combined with natural enzymes to immediately break down all types of organic waste for effective digestion. Regular applications are necessary to replenish the beneficial bacteria and minimize growth of unwanted bacteria that produce odors and noxious gas. These beneficial bacteria cultures are vastly superior to naturally occurring bacteria in digesting waste. Treated systems will reduce BOD and COD faster and more efficiently, enabling the system to treat higher volumes of waste and meet stringent effluent quality requirements. It will help the treatment system to resist temporary disruptions caused by toxic influent, while reducing odors and sludge volume. In both aerobic and anaerobic sludge digesters, digestion is more complete for less volume, easier dewatering and higher nutrient value.

Uses:

- Sewage systems
- Trickling filters
- Oxidation tanks
- Digesters
- Settling tanks
- Lagoons
- Imhoff tanks

Effective Against

- Odor
- Digests waste

- Grease
- Reduces sludge

Features and Benefits

- Attack, liquefy and remove grease, fat and oil faster
- Contains both anaerobic (can live in airless environments) and facultative (can live with or without oxygen) bacteria
- Bacteria are in spore form for extended shelf life
- Contains vitamins to enhance bacterial growth

Properties

Appearance	Powder
Fragrance	Yeast-Like
Colony count	1 Billion / Gram
Environmentally safe	Yes
Breaks down fats & grease	Lipase
Breaks down proteins	Protease
Breaks down cellulose	Cellulase
Breaks down carbohydrates & starch	Amylase

Directions: Complete directions on product label

Activate the bacteria and enzymes in warm water before using. Trickling Filter: Initial treatment 6-12 lb per MGD. Maintenance treatment 3-6 lb per MGD weekly.

Oxidation tanks: Initial Treatment: 3-6 pounds per MGD of liquid

sewage.

Aerobic and Anaerobic Digesters: 2 pounds per 1000 cubic feet

sludge weekly.

Laterals: 1 pound per 500 cubic feet for 8-inch pipe.

Ingredients	CAS Number
Sodium Chloride	7647-14-5
Yeast Culture	No CAS Number
Sodium Bicarbonate	144-55-8
Bacillus genus	68038-68-6
Yellow Prussiate of Soda	13601-19-9

Safety

Keep out of reach of children.

Quantities

100 pounds 50 pounds 25 pounds 6x1.75 pound jar

DOT Shipping (ground transportation)

Proper Shipping Name: None Class: None ID Number: None Package Group: None

