## **DIRECTIONS:**

Wear protective gloves, face mask, splash proof goggles; and other protective clothing to avoid eye or skin contact.

Pour small amount into drain at manhole opening making sure all precautions are taken to avoid injury. After 15 minutes run plenty of water through drain. Use sewer solvent at regular intervals to keep sewers open. Do not stand over opening after pouring in the solution.

DO NOT ADD HOT WATER.
DO NOT USE AROUND OPEN FLAME.

**WARNING:** Careless use can cause SEVERE BURNS TO SKIN and EYES.

**STORAGE:** Store in a cool dry place. Keep container closed when not in use.

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold as is and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose or otherwise.

## EXTREME HEAT

GRANULAR SEWER SOLVENT

DANGER: POISON/CORROSIVE KEEP OUT OF REACH OF CHILDREN.

**NET WEIGHT: 50 LBS (22.7 K)** 

**REORDER FROM:** 

G Oldstar Products Inc.
P.O. BOX 291630 - DAVIE, FL 33329
1-800-239-5699
Tax ID # 65-0597470

**EXPOSURE:** Severity of injury depends largely on product concentration and duration of exposure. Immediate action is necessary to limit severity of injury. Can cause minor irritation to severe burns and tissue damage to exposed areas of the body. May be harmful or fatal if swallowed.

**CAUTION:** It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.

FIRST AID: Inhalation: Move to fresh air. Consult physician if symptoms persist. Skin: Remove contaminated clothing and wash with plenty of soap and water. Eyes: Flush eyes immediately with large amounts of water for 15 minutes, lifting the eyelids occasionally. Get medical attention. Ingestion: Give large quantities of water then several glasses of milk. Get medical attention immediately. Do not induce vomiting.

**INGREDIENTS (CAS#):** Sodium Hydroxide (1310-73-2), Sodium Nitrate (7631-99-4), Sodium Chloride (7647-14-5), Aluminum (7429-90-5).

**HMIS RATINGS:** 

