

sewer solvent

Sewer Solvent is excellent for opening sewers clogged by grease, rags, paper and other organic material.



HIGHLIGHTS

- Temperature of 20% aqueous solution: **215° F**
- Time to reach maximum temperature: **1 min. 30 sec.**
- Time to sustain temperature of 180°F: **7 min.**


TYPICAL PROPERTIES

- Sodium Hydroxide (granulated caustic): **67%**
- pH (1% solution): **12.9-13.2**
- Aluminum: **8%**
- Appearance: **Red granular**
- Odor: **Odorless**
- Bulk Density: **72-80 lbs/ft.**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product.
- Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.

HMIS RATINGS



Red Hot Sewer Solvent

Red Hot Sewer Solvent is a strong alkaline compound used in opening sewers and drains by reacting quickly on grease, rags, paper, and other organic material. Heats up rapidly and “burns” for several minutes. Outstanding for use as a preventative maintenance product that will save time, labor, and money.

DIRECTIONS:

- Wear protective gloves, face mask, splash proof goggles; and other protective clothing to avoid eye or skin contact.
- Pour small amount into drain at manhole opening making sure all precautions are taken to avoid injury.
- After 15 minutes run plenty of water through drain.
- Use sewer solvent at regular intervals to keep sewers open.
- Do not stand over opening after pouring in the solution.
- DO NOT ADD HOT WATER.
- DO NOT USE AROUND OPEN FLAME.
- **WARNING: Careless use can cause SEVERE BURNS TO SKIN and EYES.**



NSF L1 Registered,
meets USDA 1998
L1 Guidelines
NSF Reg. No. 134728
Product Category: L1