

DESCRIPTION

This product is a clear, odorless liquid that can be applied to nearly any non-porous surface to provide a protective barrier against graffiti. After it's applied, it dries to a clear film which protects against spray paint, marker, pen, and other substances. Once defaced, the barrier is easily removed with no damage to the surface. The thickened formula adheres to vertical surfaces, and is water-resistant, allowing for outdoor applications. It will not affect signs' reflective properties, and will not yellow.

Ideal for use on enameled, powder coated, electroplated, and solid plastic surfaces, including signs, lockers, bathroom partitions, vending machines, doors, walls, windows, mirrors, and surfaces that cannot be repainted if defaced.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

REPEL IT ALL

Sacrificial Graffiti-Protection Barrier

- CREATES A CRYSTAL-CLEAR BARRIER TO PROTECT SURFACES FROM GRAFFITI
- PAINTABLE LIQUID FORMULA CAN BE APPLIED TO MOST ANY NON-POROUS SURFACE
- IDEAL FOR SIGNS, PARTITIONS, WALLS, AND SURFACES THAT CANNOT BE REPAINTED
- WATER-RESISTANT FORMULA
- PEELABLE AND RINSABLE FOR EASY REMOVAL

KEEP OUT OF REACH OF CHILDREN



Reorder From:

Goldstar Products Inc.

1-800-239-5699

Tax ID # 65-0597470

DIRECTIONS

Mix well before using. Using a roller or paint brush, apply a layer onto a clean, non-porous surface and allow to dry to a clear film "barrier". On vertical surfaces, rolling may be preferred over brushing in order to prevent the product from running. Start at the bottom and work up.

Allow up to 1 hour dry time. If the barrier becomes defaced, simply remove the film by peeling or with a water rinse and agitation. Reapply a new barrier once the surface has dried.

One gallon covers 350 to 400 square feet.

Do not store product or apply product at temperatures at or below freezing. After product has dried, freezing does not affect performance. Always test in an inconspicuous area first.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Vinyl Alcohol Polymer/25213-24-5; Poly Glycol Ester/Proprietary; Process Aids/Mixture; Triethanolamine/102-71-6; Methanol/67-56-1



Please Recycle.