

RUST OFF

STOPS, CONVERTS & INHIBITS RUST

**PROTECT AGAINST
FUTURE CORROSION**

NON-FUMING

DIRECTIONS

This rust converter instantly bonds with rust, stops its growth, transforms it into a non-rusting paintable surface, and prevents future rust formation. This rust converter provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resist the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: Shake or stir well before using. This product is ready-to-use. Do not dilute. Apply this product using a brush or roller. Apply a second coat to ensure complete transformation of rusty surfaces. **COVERAGE:** 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

IMPORTANT: Do NOT return unused material to original containers.

