

SURE START

STABILIZES FUEL

PREVENTS RUST & CORROSION

CLEANS MOTOR & PARTS

Concentrated anti-gel product to keep all types of fuel and diesel oils flowing in cold weather. By interfering with the formation of wax crystals in the fuel, the pour point of the fuel can be reduced by as much as 25 degrees. Fuel flows easily through lines and filters without the need for tank heaters. Eliminates dangerous failures of oil fired boilers, furnaces, and diesel truck and generator engines in cold weather. When used as directed this product will produce more power and efficiency, less smoke, reduce moisture and sludge in fuel. This product cleans varnish from the moving parts of the transfer pumps and injector system, it cleans injectors, fuel pumps and filters. Results in uniform spray pattern, gives even burning and easy starting.

DIRECTIONS (Cold Weather Treatment)

Add to all grades of fuel at the rate of 1 pint per 150 gallons or 1 gallon per each 1200 gallons of fuel. This dosage will lower the pour point of most residue fuels by approximately 25 degrees. In some cases additional treatment will lower the pour point by several more degrees. For best results the fuel should be at least 10 degrees F. above normal pour point when anti-gel additive is blended in.

DIRECTIONS (WARM Weather Treatment)

1. Pour 1 gallon of product for each 1600 gallons of fuel in storage tank.
2. For fuel tanks on equipment add 1 pint for every 200 gallons of fuel.

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles (on-road) and non-road engines

DANGER

Hazard Statements:

Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary Statements:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. -- No smoking. Keep container tightly closed. Ground / bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Avoid breathing mist / vapours. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/ attention.

Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up. P501: Dispose of contents and container in accordance with local regulations.

HMS Hazard ID: Health:2 Flammability:2 Reactivity:0

Manufactured by: Clean Concepts/MultiFunctional Diesel Fuel Additive

