Company : Codistar Products Davie, FI: 33329-USA Company : Code Star Star Star Company : Code Star Star Star Code Star Star Star Code Star Star Star Code Star Star Code Star Star Code St	SECTION 1: Product and co	mpany identification
Lice meller Product code Same Company Company Code 2019 Company Company Code 2019 Company Code 2019 Company Code 2019 Company Code 2019 Code 2019 Co	Product name :	W.D.C.
Company : Coddstar products Davie, FL 33339- USA T (200) 238-5696 Emergency number : Chemiter: (800) 424-9300 SECTION 2: Hazards Identification 2.1. Classification of the substance or instrue CMS-VS classification File and the substance of the substance or instrue CMS-VS classification File and the substance or instrue CMS-VS classification File and the substance of the substance or instrue CMS-VS classification File and the substance of the	Use of the substance/mixture :	
P.O. Box 291630 Davie, FL 3323 - USA T (800) 239-5639 Emergency number : Chemter: (800) 424-9300 SCTION 2: Hazards identification 2.1. Classification of the substance or mixture GMS-US classification of the substance or mixture GMS-US classification of the substance or mixture Compressed gas H220 Acute Tox 3 (Toria) H 430 Acute Tox 4 (Toria) H 430 Acute	Product code :	8209
SUTION 2: Hazards identification 2.1. Classification of the substance or mixture GHS-US classification Film. Aerosol 1: H222 Compressed gas H280 Acute Tox 3 (Coran) H301 Acute Tox 3 (Chernal) H301 Full text of H statements: see section 16 2.2. Label cleanests CHSUB GHS-US Genow Genow Genow Genow Signal word (GHS-US) : Danger Genow Genow<	Company :	P.O. Box 291630 Davie, FL 33329 - USA
2.1. Classification of the substance or mixture GHS-US classification Fign. Acrosol H222 Compressed gas H280 Acute Tox 3 (Oran) H301 Acute Tox 3 (Oran) H301 Acute Tox 3 (Oran) H301 Acute Tox 3 (Oran) H301 STOT SE 1 H370 Full text of H statements : see section 16 2.2. Label clements GHS-US labeling Hazard pictograms (GHS-US) : Descent H302 GHS0 GHS0 Signal word (GHS-US) : Descent H302 GHS0 GHS0 Signal word (GHS-US) : Descent H302 Contains gas under pressure: may explode if heated Toxic if swallowed, in contact with skin of i linhaled Causes damage to organs (central nervous system, cardiovascular system, eyes, respiratory system, Skin, digestive Hacit, Sparks, open flames, hot surfaces. No smoking Do not breath leme, mist, sparks, open flames, hot surfaces. No smoking Do not breath leme, mist, sparks, open flames, hot surfaces. No smoking Do not breath leme, mist, spray, vapors Avoid breathing fume, PON CHTER, a choord, Do NOT induce vomiting If exposed: Cail a policor centre/doctor Cail a polison centre/doctor Cail a polison centre/doctor Cail a polison centre/doctor Cail a polison center/doctor Cail a polison center/doctor C	Emergency number :	Chemtec: (800) 424-9300
GHS-US classification H222 Compressed gas Acute Tox 3 (Oral) H280 Acute Tox 3 (Oral) Acute Tox 3 (Oral) H311 Acute Tox 3 (Oral) H311 H370 Full text of H statements : see section 16 E 22. Label elements E GHS-US labeling Hazard pictograms (GHS-US) : : Hazard pictograms (GHS-US) : : Signal word (GHS-US) : : Hazard statements (GHS-US) : : Ferre autor in the intermediate in the intermediate	SECTION 2: Hazards identif	ication
Fiam. Aerosol 1 H222 Compressed gas H280 Acute Tox 3 (Orman) H301 Acute Tox 3 (Orman) H301 STOT SE I H310 EXPLOSE SECOND H301 STOT SE I H310 Acute Tox 3 (Orman) H301 Acute Tox 4 (Orman) H301 Acute	2.1. Classification of the substar	ice or mixture
Compressed gas H280 Anate Tox 3 (Oral) H301 Anate Tox 3 (Oral) H301 Anate Tox 3 (Inhalation.gas) H331 STOT SE 1 H301 Full text of H statements : see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) : : : : : : : : : : : : : : : : : : :	GHS-US classification	
 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) : i i i i i i i i i i i i i i i i i i	Compressed gasH28Acute Tox. 3 (Oral)H30Acute Tox. 3 (Dermal)H31Acute Tox. 3 (Inhalation:gas)H33	0 1 1 1
GHS-US labeling Hazard pictograms (GHS-US) : i i i i i i i i i i i i i i i i i i i	Full text of H statements : see sect	ion 16
Hazard pictograms (GHS-US) : : : : : : : : : : : : : : : : : : :	2.2. Label elements	
 Signal word (GHS-US) Hazard statements (GHS-US) E Zhremely flammable aerosol Contains gas under pressure; may explode if heated Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs (central nervous system, cardiovascular system, eyes, respiratory system, Skin, digestive tract) Precautionary statements (GHS-US) Keep away from heat, sparks, open flames, hot surfaces, No smoking No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Do not treathe fume, mist, spray, vapors Avoid breathing fume, mist, spray, vapors Wash thoroughly after handling Do not early avant or or in a well-ventilated area Wear protective gloves, protective clothing, eye protection If swallowed: Immediately call a POISON CENTER Call a poison center/doctor Call a doctor, a POISON CENTER Call a POISON CENTER Call a poison center/doctor Call a doctor if you feel unwell Specific treatment (see First aid measures on this label) Rinse mouth Take of immediately all contaminated clothing Wash contaminated clothing before reuse Store in a well-ventilided place. Keep container tightly	-	
 Hazard statements (GHS-US) : Extremely flammable aerosol Contains gas under pressure; may explode if heated Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs (central nervous system, cardiovascular system, eyes, respiratory system, Skin, digestive tract) : Keep away from heat, sparks, open flames, hot surfaces, No smoking No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Do not breathing fume, mist, spray, vapors Avoid breathing fume, mist, spray, vapors Wash thoroughly after handling Do not serve (Innex of the context) was even using this product Use only outdoors or in a well-ventilated area Wear protective gloves, protective cothing, eye protection If swallowed: Inmediately call a POISON CENTER, a doctor, Do NOT induce vomiting If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water If inhaled: Remove person to fresh air and keep comfortable for breathing If exposed: Call a poison center/doctor Call a doctor, a POISON CENTER Call a DOISON CENTER Call a DOISON CENTER Call a OOSIN CENTER Call a OCIST, a doctor if you feel unwell Specific treatment (see First ald measures on this label) Rinse mouth Take off immediately all contaminated clothing Wash contaminated clothing before reuse Store in a well-ventilated place. Keep container tightly closed Store in a well-ventilated place. Keep container tightly closed Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Store in a well-ventilated place Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Dispose of contents/container to comply with local/regional/national/international regulations 	Signal word (GHS-US)	
Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Do not breathe fume, mist, spray, vapors Avoid breathing fume, mist, spray, vapors Wash thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Wear protective gloves, protective clothing, eye protection If swallowed: Immediately call a POISON CENTER, a doctor, Do NOT induce vomiting If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water If inhaled: Remove person to fresh air and keep comfortable for breathing If exposed: Call a poison center/doctor Call a doctor, a POISON CENTER Call a doctor, a POISON CENTER Call a DOISON CENTER Call a OCION, ENTER Call a OCION, ENTER Call a Cotor in you feel unwell Specific treatment (see First aid measures on this label) Rinse mouth Take off immediately all contaminated clothing Wash contaminated clothing before reuse Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Dispose of contents/container to comply with local/regional/national/international regulations 2.3. Other hazards	Hazard statements (GHS-US)	 Extremely flammable aerosol Contains gas under pressure; may explode if heated Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs (central nervous system, cardiovascular system, eyes, respiratory
	Precautionary statements (GHS-U	Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Do not breathe fume, mist, spray, vapors Avoid breathing fume, mist, spray, vapors Wash thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Wear protective gloves, protective clothing, eye protection If swallowed: Immediately call a POISON CENTER, a doctor, Do NOT induce vomiting If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water If inhaled: Remove person to fresh air and keep comfortable for breathing If exposed: Call a poison center/doctor Call a doctor, a POISON CENTER Call a POISON CENTER Call a POISON CENTER, a doctor if you feel unwell Specific treatment (see First aid measures on this label) Rinse mouth Take off immediately all contaminated clothing Wash contaminated clothing before reuse Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Store in a well-ventilated place Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
	2.3 Other hazards	
	No additional information available	

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

3.1. Substance Not applicable

Full text of H-phrases: see section 16

3.2 Mixture

Name	Product identifier	%	GHS-US classification
methanol	(CAS No) 67-56-1	90 - 100	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	1 - 10	Not classified
1,2-propanediol	(CAS No) 57-55-6	1 - 10	Not classified

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

:	If you feel unwell, seek medical advice (show the label where possible).
:	Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen if necessary. Respiratory problems: consult a doctor/medical service.
:	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
:	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
:	Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Never give anything by mouth to an unconscious person.
ects,	both acute and delayed
:	Extremely flammable. Contents under pressure. Depression of the central nervous system. May be fatal if swallowed and enters airways. Causes damage to organs (central nervous system, cardiovascular system, eyes, Skin). Toxic if swallowed, in contact with skin or if inhaled.
:	Central nervous system depression. Repeated exposure by inhalation or skin absorption may cause systemic poisoning, brain disorders, and blindness. Toxic if inhaled. May cause drowsiness or dizziness. Headache.
:	Toxic in contact with skin. May cause irritation to skin.
:	May cause severe irritation.
:	May be fatal if swallowed and enters airways. MAY BE FATAL IF SWALLOWED. May be harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.
	: : : : :

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media Suitable extinguishing media	: Water fog. Dry chemical powder. Carbon dioxide.
5.2. Special hazards arising from the sub	ostance or mixture
Fire hazard	: Flammable aerosol. Under fire conditions closed containers may rupture or explode.
Explosion hazard	 vapors may travel long distances along ground before igniting/flashing back to vapor source. Contains gas under pressure; may explode if heated. Bursting aerosol containers may be propelled from a fire at high speed.
Reactivity	: Upon combustion: CO and CO2 are formed.
5.3. Advice for firefighters	
Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.
Special protective equipment for fire fighters	 Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

W.D.C.

Safety Data Sheet

SECTION 6: Accidental release n	ieasures
6.1. Personal precautions, protective	equipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground. No flames, no sparks. Eliminate all sources of ignition. No open flames. No smoking.
6.1.1. For non-emergency personnel	
Protective equipment	: Do not enter without an appropriate protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. No open flames, no sparks, and no smoking.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.
6.2. Environmental precautions	
· ·	s. Do not allow to enter drains or water courses.
6.3. Methods and material for contain For containment	 ment and cleaning up Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of ignition. Use water spray to disperse the vapors. Collect spillage.
Methods for cleaning up	: Take up liquid spill into inert absorbent material.
6.4. Reference to other sections No additional information available	
SECTION 7: Handling and storag	e
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	: Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Avoid breathing vapors, mist. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source.
Safe use of the product	: Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal.
7.2. Conditions for safe storage, includ	ling any incompatibilities
Technical measures	: Do not puncture, incinerate or crush.
Storage conditions	: Store locked up. Keep container tightly closed. Store in a dry place. Store in a well-ventilated place. Keep out of reach of children.
Incompatible products	: Strong acids. alkalis. Oxidizing agents.
Incompatible materials	: Sources of ignition. Heat sources. Open flame.
Heat-ignition	: KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Storage area	: Store in a cool area. Store away from heat. Aerosol 1.
SECTION 8: Exposure controls/p	bersonal protection

methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
carbon dioxide, liqu	iefied, under pressure (124-38-9)	
ACGIH	ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	30000 ppm (Carbon dioxide; USA; Short time value; TLV - Adopted Value)

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station.

Personal protective equipment

Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Protective goggles. Protective apron.



SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and chemical	. .		
Physical state	: Gas		
Appearance	: Aerosol. clear. Liquid.		
Odor	: Solvent-like odor		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: No data available		
Freezing point	: No data available		
Boiling point	: No data available		
Flash point	: 52 °F (liquid portion)		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: No data available		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Specific gravity / density	: 0.8 g/ml		
Solubility	: Soluble in water.		
Log Pow	: No data available		
Log Kow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
VOC content	: > 95 %		

:

SECTION 10: Stability and reactivity 10.1. Reactivity Upon combustion: CO and CO2 are formed. 10.2. Chemical stability Stable under normal conditions. 10.3. Possibility of hazardous reactions Hazardous polymerization does not occur. 10.4. Conditions to avoid Heat. No flames, no sparks. Eliminate all sources of ignition. Welding. Open flame. Direct sunlight. **10.5.** Incompatible materials Strong acids. alkalis. Oxidizing agents. 10.6. Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced. **SECTION 11: Toxicological information** 11.1. Information on toxicological effects Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:gas: Toxic if inhaled. methanol (67-56-1) LD50 dermal rabbit 12800 mg/kg

methanol (67-56-1)	
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	128.200 mg/l/4h
ATE CLP (dust, mist)	0.500 mg/l/4h
1,2-propanediol (57-55-6)	
LD50 oral rat	20000 mg/kg (Rat; Experimental value)
LD50 dermal rat	22500 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	20800 mg/kg (Rabbit; Experimental value)
ATE CLP (oral)	20000.000 mg/kg body weight
ATE CLP (dermal)	20800.000 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Causes damage to organs (central nervous system, cardiovascular system, eyes, respiratory system, Skin, digestive tract).
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.
Symptoms/injuries after inhalation	: Central nervous system depression. Repeated exposure by inhalation or skin absorption may cause systemic poisoning, brain disorders, and blindness. Toxic if inhaled. May cause drowsiness or dizziness. Headache.
Symptoms/injuries after skin contact	: Toxic in contact with skin. May cause irritation to skin.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. MAY BE FATAL IF SWALLOWED. May be harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.
Likely routes of exposure	: Inhalation:Eves:Dermal:Ingestion

12.1. Toxicity	
carbon dioxide, liquefied, under pressure (124-38-9)
LC50 fish 1	35 mg/l (LC50; 96 h; Salmo gairdneri)
1,2-propanediol (57-55-6)	
EC50 Daphnia 1	34400 mg/l (EC50; 48 h)
LC50 fish 2	51600 mg/I (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss)
12.2. Persistence and degradability	
carbon dioxide, liquefied, under pressure (124-38-9)
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
1,2-propanediol (57-55-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.96 - 1.08 g O□/g substance
Chemical oxygen demand (COD)	1.63 g O□/g substance
ThOD	1.69 g O□/g substance
BOD (% of ThOD)	0.57

Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.
1,2-propanediol (57-55-6)	
Log Pow	-1.410.30 (-0.92; Experimental value; -1.07; Experimental value; Equivalent or similar to OECD 107; 20.5 °C)
Bioaccumulative potential	Not bioaccumulative.

13.1. Waste treatment methods Waste disposal recommendations

: This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). . Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information Department of Transportation (DOT) Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1 UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols flammable, (each not exceeding 1 L capacity) Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115 Hazard labels (DOT) : 2.1 - Flammable gas DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306 173.xxx) DOT Quantity Limitations Passenger : 75 kg aircraft/rail (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft : 150 kg only (49 CFR 175.75) DOT Vessel Stowage Location : A DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials **Additional information** Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306. ADR No additional information available Transport by sea No additional information available Air transport No additional information available **SECTION 15: Regulatory information** All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. methanol CAS No 67-56-1 90 - 100%

methanol (67-56-1)

methanol (67-56-1)	
Subject to reporting requirements of United States	SARA Section 313
CERCLA RQ	5000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information


Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

NFPA health hazard	:	2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	:	4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity	:	0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.