

FITTING INSTRUCTIONS: Garage door Top Seal (WS015)

Tools required:

- Tape measure
- Scissors
- Hacksaw
- Pencil
- Drill

Kit includes:

- Top seal
- Screw and washer pack
- Fitting instructions

GaraDry™

GaraDry

Units 16-18

17 Summerwood Lane

Halsall, Ormskirk

Lancashire, L39 8RG, UK

Tel: 01704 532 360

Email: sales@garadry.co.uk

Web: uk.garadry.com

Suitable to fit with a manual or automatic up and over garage doors.

It is important to follow instructions carefully! (Must be fitted by an adult over the age of 18) Work is undertaken at the purchaser's own risk.

STEP ONE

With a tape measure, measure the opening from wooden post to wooden post at the top of the garage door. Do not measure the width of the garage door.

STEP TWO

Make a mark with a pencil on the Weather Stop Top Seal where the seal needs to be cut to fit the opening. Using scissors first cut the rubber part of the seal then with a hacksaw cut the plastic part of the seal to size.

STEP THREE

With the garage door shut and in the locked position, hold the Weather Stop Top Seal in place making sure there is a tight seal. Then mark with a pencil the under head of the frame where the Top Seal will fit.

STEP FOUR

With a pencil make a mark approximately every 300mm. Using a 6mm drill bit, drill holes through the top seal where you have made marks on the top seal. Make sure you remove any excess plastic to make a clean hole.

(By creating a drilled hole that is slightly bigger than the screw allows room for the plastic top seal to expand in the summer months and contract in the cold winters)

STEP FIVE

With the garage door half open, position the Garage Door Top Seal where you have marked the frame. Then put the washer over the screw and then put screw through the hole in the top seal and then fix the screw into the head of the frame. Continue this process until the top seal is secured tightly.

(TIP When fixing the top seal, another person holding the other end of the seal while you tighten the screws, will make the task easier) Close the garage door and make sure the door shuts and locks properly.

