The Ultimate Compact, Foldable Travel Scooter





Scooter folded

Ready for transport and easily folded, the 4-wheel **Quest Folding Scooter** is perfect for the active lifestyle. Offering great performance indoors and out at a maximum speed of 6 km/h (4 mph) and a range per charge of up to 20 km (12.5 miles), the Quest Folding Scooter delivers a comfortable and convenient ride. A great space saver that adjusts to fit perfectly inside any wardrobe or vehicle boot, the Quest Folding Scooter is sleek, compact, and extremely easy to operate.

PRIDE[®] MOBILITY SCOOTERS LIVE YOUR BEST[®]

Visit pridemobility.com.au to learn more

Quest Folding Scooter Specifications

Weight Capacity	115 kgs (250 lbs.)
Maximum Speed ¹	Up to 6 km/h (4 mph)
Ground Clearance ²	6 cm (2.3")
Turning Radius ²	82 cm (32")
Overall Length ²	93 cm (37")
Overall Width ²	48.5 cm (19")
Front Tyres ²	4 x 18 cm (1.6" x 7") solid
Rear Tyres ²	5 x 20 cm (2" x 8") solid
Range Per Charge ^{1,4}	Up to 20 km (12.5 miles)
Total Weight Without Batteries ⁵	23.5 kg (51.4 lbs.)
Heaviest Piece When Disassembled	23.5 kg (51.4 lbs.) (unit does not disassemble - unit weight without battery pack)
Standard Seating	Type : Foldable, vinyl-covered, molded plastic Material : Grey vinyl Dimensions : Width: 41 cm (16") Depth: 33 cm (13")
Battery Requirements ⁵	(1) 24-volt (Lithium-ion) Size: (1) 11.5 AH (Lithium-ion) Weight : 11.5 AH (Lithium-ion) Each 2.3 kg (5 lbs.) (One Required)
Battery Charger	Off-board, 2.5 amp
Colour Options	

All specifications provided by Heartway[®] Medical Products. Product distributed by Pride Mobility[®].



A REAL PROPERTY IN CONTRACTOR OF STREET, STREE **PRIDE® MOBILITY SCOOTERS** LIVE YOUR BEST®

20-24 Apollo Drive Hallam, Victoria 3803 ACN 088 609 661 ABN 66 088 609 661 (Tel) 03 8770 9600 • (Fax) 03 9703 2720 www.pridemobility.com.au

Features

- Unique folding design
- Folds in just three easy steps •
- Adjustable tiller
- Up to 20 km (12.5 miles) range per charge
- Easy to transport at home, hotels, or airports
- Can be stowed upright or laid down
- Articulated front end adds greater stability •
- Front and rear LED lighting

TO FOLD:

TO UNFOLD:













Fold and Lock Tiller

- Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- Due to manufacturing tolerances and continual product improvement. this specification can be subject to a variance of (+ or - 3%). 3 AGM or gel cell type required.
- Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

