

END-TO-END | Scooter Specifications

For more information visit pridemobility.com.au or call 03 8770 9600
20-24 Apollo Drive, Hallam VIC 3803 | ACN 088 609 661 | ABN 66 088 609 66



MODEL NAME	Quest®	Go-Go®Ultra X	Go-Go® Elite Traveller Plus	Go-Go® LX w/ CTS Suspension	Revo® 2.0	Zero Turn 8	Zero Turn 10	Pathrider® ES 10	Pathrider® 10	Pathrider® 10 DX	Gopher SV	Victory® LX w/ CTS Suspension	Celebrity® DX	Celebrity® XL DX	Pathrider® 130 XL	Pathrider® 140 XL	Outback®	Sport Rider
FRONT TYRES	4 cm x 18 cm (1.5"x 7") solid	3W: 5 cm x 20.3 cm (2"x 8") solid 4W: 5 cm x 17.8 cm (2"x 7") solid	5 cm x 20.3 cm (2"x 8") solid	5 cm x 17.8 cm (2"x 7") solid	6.3 cm x 22.8 cm (2.5"x 9") solid	5 cm x 17.8 cm (2"x 7") solid	22.8 cm x 7 cm (9"x 2.75") solid	9.1 cm x 26.4 cm (3.6"x 10.4")	9 cm x 25.4 cm (3.5"x 10")	9 cm x 25.4 cm (3.5"x 10")	7.62 cm x 25.4 cm (3"x 10")	9 cm x 25.4 cm (3.5"x 10")	9 cm x 25.4 cm (3.5"x 10")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	37 cm x 15.2 cm (14.5"x 6")	6.9 cm x 48.2 cm (2.75"x 19") ¹⁷
REAR TYRES	5 cm x 20 cm (1.9"x 7.8") solid	6.35 cm x 20.3 cm (2.5"x 8") solid	7.6 cm x 22.9 cm (3"x 9") solid	6.35 cm x 20.3 cm (2.5"x 8") solid	6.3 cm x 22.8 cm (2.5"x 9") solid	6.35 cm x 22.9 cm (2.5"x 9") solid	27.3 cm x 8.25 cm (10.75"x 6") solid	9.1 cm x 27.3 cm (3.6"x 10.75") solid	9 cm x 25.4 cm (3.5"x 10")	10 cm x 25.4 cm (4"x 10")	7.62 cm x 25.4 cm (3"x 10")	9 cm x 25.4 cm (3.5"x 10")	10 cm x 25.4 cm (4"x 10")	10 cm x 25.4 cm (4"x 10")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	37 cm x 15.2 cm (14.5"x 6")	6.9 cm x 48.2 cm (2.75"x 19") ¹⁷
MAXIMUM SPEED ¹⁸	Up to 6 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 7 km/h (4.4 mph)	Up to 8 km/h (5 mph)	Up to 6.4 km/h (4 mph)	Up to 10 km/h (6.2 mph)	Up to 8.85 km/h (5.5 mph)	Up to 8.4 km/h (5.25 mph)	Up to 8.85 km/h (5.5 mph)	Up to 10 km/h (6.2 mph)	Up to 9 km/h (5.6 mph)	Up to 9.65 km/h (6 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)
GROUND CLEARANCE ^{4,13,15}	5.8 cm (2.3") at frame	6.3 cm (2.5") at midframe 3.8 cm (1.5") at motor	7.62 cm (3") at frame	6.4 cm (2.5") at frame 3.8 cm (1.5") at motor	8.9 cm (3.5") at frame 3.2 cm (1.25") at motor	8.9 cm (3.5") at frame 1.3" at motor	5 cm (2") at motor	8.8 cm (3.5") at frame	7.6 cm (3") at midframe	8.25 cm (3.25") at midframe	4 cm (1.5") at rear frame	5.6 cm (2.2") at motor	8.25 cm (3.25")	10.8 cm (4.25")	19.7 cm (3.8")	13.3 cm (5.25") at midframe	14 cm (5.5") at motor	12.7 cm (5") at shroud
TURING RADIUS ⁴	82 cm (32")	3W: 83.8 cm (33") 4W: 112 cm (44")	116.2 cm (45.72")	116.2 cm (45.72")	132.1 cm (52")	97.2 cm (38.25")	109 cm (43")	132 cm (51.9")	137 cm (53.9")	133.3 cm (52.5")	143 cm (56.2")	152 cm (59.9")	3W: 105.4 cm (41.5") 4W: 149.8 cm (59")	168.2 cm (66.2")	170 cm (67")	210 cm (83") right 208 cm (82") left	243 cm (95.6")	3W: 158 cm (62.2")
LENGTH & WIDTH ^{4,12}	92.7 cm/49.5 cm (36.5"/19.5")	3W: 94 cm/49.5 cm (37"/19.5") 4W: 100.3 cm/49.5 cm (39.5"/19.5")	102.3 cm/54 cm (40.25"/21.25")	104 cm/52.1 cm (41"/20.5")	119.4 cm/52.7 cm (47"/20.75")	116 cm/50.8 cm (45.75"/20")	122 cm/61.6 cm (48"/24.25")	115.6 cm/57.1 cm (45.5"/22.5")	115 cm/56.5 cm (45.25"/22.25")	119.4 cm/56.2 cm (47"/22.13")	119 cm/59 cm (46.8"/23.2")	119.4 cm/56.5 cm (47"/22.25")	3W: 116.8 cm/61 cm (46"/24") 4W: 118.7 cm/61 cm (46.75"/24")	130.2 cm/64.1 cm (51.25"/25.25")	136 cm/63.6 cm (53.5"/25")	142.8 cm/69.2 cm (56.25"/27.25")	156 cm/83 cm (61.4"/32.6")	3W: 165 cm/78 cm (65"/30.7")
SEAT-TO-GROUND HEIGHT RANGE	51 cm (20") Fixed	55 cm - 60 cm (21.6" - 23.6")	52 cm - 55.88 cm (20.5" - 22")	52.7 cm - 56.5 cm (20.75" - 22.25")	53.3 cm - 60 cm (21" - 23.5")	53.3 cm - 60 cm (21" - 23.5")	58.4 cm - 63.5 cm (23" - 25")	51.4 cm - 55.2 cm (20.25" - 21.75")	52 cm - 55.8 cm (20.5" - 22")	60 cm - 63.8 cm (23.6" - 25.1")	61 cm - 64 cm (24" - 25.2")	60 cm - 64.8 cm (23.5" - 25.5")	58.5 cm - 61.5 cm (23" - 24.25")	54 cm - 64 cm (21.25" - 25.25")	56.7 cm (22.3")	66.7 cm - 70.5 cm (26.25" - 27.75")	76 cm - 80 cm (30" - 31.5")	63 cm (24.8")
SEAT TYPE (STANDARD) ⁶	Compact, Foldable, Molded Plastic 41 cm x 33 cm (16"x 13")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Foldable Molded Plastic 46 cm x 43 cm (18"x 17")	Foldable Molded Plastic 46 cm x 43 cm (18"x 17")	CRS Junior Seat 44.25 cm x 43 cm (17.5"x 17")	Foldable Molded Plastic 48 cm x 42 cm (19"x 16.5")	Reclining H/B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Captains High-Back Adjustable Seat 51 cm x 56 cm (20"x 22")
WEIGHT ^{3,4,14}	4W: 23.5 kg (51.8 lbs)	3W: 34.5 kg (76 lbs) 4W: 36.3 kg (80 lbs)	4W: 39.4 kg (87 lbs)	4W: 39.4 kg (87 lbs)	4W: 60 kg (132 lbs)	4W: 53.9 kg (119 lbs)	4W: 82.1 kg (180 lbs)	4W: 59.4 kg (130.9 lbs)	4W: 62.4 kg (137.5 lbs)	4W: 84.8 kg (186.9 lbs)	4W: 68.9 kg (151.8 lbs)	4W: 81.2 kg (179 lbs)	3W: 70.7 kg (156 lbs) 4W: 75 kg (165 lbs)	4W: 112 kg (246.9 lbs)	4W: 99.8 kg (220 lbs)	4W: 117.7 kg (259 lbs)	4W: 124 kg (273 lbs)	3W: 115 kg (253.5 lbs)
SEAT-TO-DECK HEIGHT RANGE	31 cm (12.2") Fixed	40 cm - 43.8 cm (15.75" - 17.25")	41.3 cm - 45 cm (16.25" - 17.75")	41.3 cm - 43.8 cm (16.25" - 17.25")	38.1 cm - 45.7 cm (15" - 18")	40.6 cm - 45.6 cm (15.9" - 17.9")	47.5 cm - 52.5 cm (18.7" - 20.6")	37 cm - 42 cm (14.5" - 16.5")	43.8 cm - 47.6 cm (17.2" - 18.75")	44.5 cm - 48.3 cm (17.5" - 19")	46 cm - 49 cm (18.1" - 19.3")	42 cm - 47 cm (16.5" - 18.5")	41 cm - 44.5 cm (16.2" - 17.5")	43.2 cm - 53.3 cm (17" - 21")	47 cm (18.5")	53.3 cm - 57 cm (21" - 22.5")	50 cm - 53 cm (19.6" - 21")	47.5 cm (18.7")
BATTERY WEIGHT ¹¹	2.3 kg (5 lbs)	4.08 kg (9 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	11 kg (24.2 lbs) ea	6.05 kg (13.3 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	16.8 kg (37 lbs) ea	23.45 kg (51.6 lbs) ea	27.9 kg (61.5 lbs) ea	23.75 kg (52.3 lbs) ea
BATTERY REQUIREMENTS ⁷	(1) Lithium 11.5 AH	(2) 12AH	(2) 18AH	(2) 18AH	(2) 31AH	(2) 22AH	(2) 40AH	(2) 31AH	(2) 31AH or (2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 40 AH	(2) 31AH or (2) 40AH	(2) 40 AH	(2) 55 AH	(2) 70 AH	(2) 100 AH	(2) 70 AH
PER CHARGE RANGE (MAX) ^{2,9}	Up to 19.3 km (12 miles)	3W: Up to 11 km (6.9 miles) 4W: Up to 11.5 km (7.2 miles)	Up to 20.9 km (13 miles) ¹⁰	Up to 16.9 km (10.5 miles) ¹⁰	Up to 21 km (13 miles)	Up to 16 km (10 miles)	Up to 28.8 km (17.8 miles)	Up to 17.9 km (11 miles)	Up to 25 km (15.5 miles)	Up to 25 km (15.5 miles) with 40 AH batteries	Up to 30 km (18.6 miles)	Up to 26 km (16 miles)	Up to 20.6 km (12.8 miles)	Up to 40.2 km (24.9 miles) ¹⁶	Up to 25 km (15.5 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)
BATTERY CHARGER	Lithium Off-Board 2.5A	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3A	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A
SUSPENSION	N/A	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	3W: Rear 4W: Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
MAXIMUM WEIGHT CAPACITY	113.3 kg (250 lbs)	118 kg (260 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	160 kg (352 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)
STANDARD BODY COLOURS	White	Red	Red, Blue ¹	Red, Blue ¹	Grey Street, True Blue	Fire Opal, Pearl White, Sapphire Blue	Candy Apple Red	Red	Viper Blue	Viper Blue	Red	Candy Apple Red	Candy Apple Red	Candy Apple Red, Silver	Candy Apple Red, Mercury Silver	Candy Apple Red, Yellow, Silver	Stone Grey	Black
WEIGHT OF HEAVIEST PIECE ⁴	23.5 kg (56.2 lbs) (does not disassemble)	3W: 13.4 kg (29.5 lbs) 4W: 15.4 kg (34 lbs) (front sections)	15.4 kg (34 lbs) (front section)	16.6 kg (36.6 lbs) (front section)	25.9 kg (57 lbs) (front section)	21.8 kg (48 lbs) (rear section)	34 kg (75 lbs) (rear section)	25.8 kg (57 lbs) (front section)	27.7 kg (61 lbs) (rear section)	29.5 kg (65 lbs) (front section)	50.8 kg (112 lbs) (does not disassemble)	35.2 kg (77.6 lbs) (rear section)	3W: 27.5 kg (60.5 lbs) 4W: 32 kg (70.5 lbs) (front section)	37.6 kg (83 lbs) (front section)	34 kg (74.9 lbs) (rear section)	93 kg (205 lbs) (main frame)	99 kg (218.2 lbs) (main frame)	3W: 92.3 kg (203.4 lbs) (main frame)
3W/4W OPTION	4W	4W & 3W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W & 3W	4W	4W	4W	4W	3W

TRAVEL MOBILITY

ZERO TURN SERIES

MID-SIZED LUXURY

FULL-SIZED LUXURY

1 All shroud panels included. 2 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. 3 Battery weight not included. 4 Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. 5 12 AH battery pack weighs 8.8 kg (19.5 lbs.). 6 Durable solid plastic. 7 Deep cycle (AGM or gel cell type recommended) excluding Lithium-ion models. 8 18 AH battery pack weighs 13.4 kg (29.5 lbs.). 9 Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. 10 Up to 14 miles per charge on 18 AH batteries. 11 Battery weight may vary based on manufacturer. 12 Width of base (not including seat). 13 Does not account for anti-tip clearance. 14 Includes standard seat weight. 15 At midframe 16 Range tested with 31-36 AH Batteries. Standard larger battery size would increase range. 17 6.9 cm x 35.5 cm (2.75"x 14") Rim Only 18 Varies with user weight, terrain type, battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. NOTE The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

