



MODEL NAME	Jazzy® Passport	Go Chair NG®	Jazzy® Select 6	Jazzy® Air 2	Jazzy® 623 2.0	Jazzy® Elite HD	Jazzy® 1450	R-40
<b>WEIGHT CAPACITY</b>	113.3 kg (250 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	204.1 kg (450 lbs) <sup>6</sup>	273.1 kg (600 lbs)	136 kg (300 lbs)
<b>TURNING RADIUS<sup>1</sup></b>	61.5 cm (24.25")	64.5 cm (25.4")	55.5 cm (21.87")	61.5 cm (24.25")	50.8 cm (20")	61.9 cm (24.3")	67.3 cm (26.5")	96.5 cm (38") with foot riggings
<b>WIDTH<sup>1</sup></b>	59.6 cm (23.5")	57.1 cm (22.6")	59.6 cm (23.5")	64.1 cm (25.25")	60.9 cm (24")	61.5 cm (24.2")	74.2 cm (29.25")	63.5 cm (25") at rear wheels
<b>LENGTH<sup>1,2</sup></b>	101.6 cm (40")	83.8 cm (33")	90.1 cm (35.5")	106 cm (42")	90.1 cm (35.5")	90.1 cm (35.5")	97.1 cm (38.25")	88.9 cm (35")
<b>MAXIMUM SPEED<sup>3</sup></b>	Up to 5.7 km/h (3.6 mph)	5.9 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 6.4 km/h (4 mph)	Up to 9.6 km/h (6 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 9.6 km/h (6 mph)
<b>GROUND CLEARANCE<sup>1</sup></b>	7.6 cm (3") at motor	4.5 cm (1.8") at frame	4.4 cm (1.75") at motors & at centre frame	7.3 cm (2.9") 2.5 cm (1") at motor bracket	7.6 cm (3") at rear castor	7.6 cm (3")	3.8 cm (1.5")	7.2 cm (2.87")
<b>FRONT WHEELS</b>	20.3 cm (8") solid front castors	15.2 cm (6") solid castors	15.24 cm (6") solid castors	15.2 cm (6") solid castors	15.2 cm (6") solid castors	7.6 cm (3") solid anti-tips	10.6 cm (4") solid anti-tips	22.8 cm (9") pneumatic castors
<b>DRIVE WHEELS</b>	30.4 cm (12") pneumatic	22.8 cm (9") solid	25.4 cm (10") solid	25.4 cm (10") solid	35.5 cm (14") pneumatic	35.5 cm (14") solid	35.5 cm (14") solid	35.5 cm (14") pneumatic
<b>REAR WHEELS</b>	N/A	7.6 cm (3") solid anti-tips	15.2 cm (6") solid castors	15.2 cm (6") solid castor	15.2 cm (6") solid castors	15.2 cm (6") solid castors	22.8 cm (9") castors	7.6 cm (3") solid rear anti-tips
<b>DRIVE TRAIN</b>	2x 180W brushed motors	Two-motor, rear-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel 6 <sup>®</sup>	Two-motor, front-wheel drive	Two-motor, front-wheel drive	Two-motor, rear-wheel drive
<b>BRAKING SYSTEM</b>	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical
<b>SUSPENSION TYPE</b>	Limited	Limited	Active-Trac <sup>®</sup> (ATX)	Active-Trac <sup>®</sup> with Mid-Wheel 6 technology	Active-Trac <sup>®</sup> (ATX)	Limited	Swing Arm	Adjustable
<b>HIGH-BACK SEAT-TO-FLOOR RANGE</b>	N/A	N/A	53.9 cm - 59 cm (21.25" - 23.25")	53.9 cm - 84 cm (21.25" - 33.1")	52 cm - 59.6 cm (20.5" - 23.5")	50.8 cm - 55.8 cm (20" - 22")	52 cm - 57.1 cm (20.5" - 22.5")	N/A
<b>SPECIALITY SEATING OPTIONS</b>	N/A	N/A	N/A	N/A	Synergy <sup>®</sup> Seating <sup>A</sup> Tru-Balance <sup>B</sup>	N/A	Synergy <sup>®</sup> Seating <sup>A</sup>	N/A
<b>SPECIALTY CONTROLS</b>	N/A	N/A	N/A	N/A	Yes	N/A	Yes	N/A
<b>STANDARD ELECTRONICS</b>	50A, PG VSI	40A, PG GC3	40A, PG GC3	40A, VR2	90A, PG VR2	90A, PG VR2	90A, PG VR2	70A, PG VR2
<b>BATTERY SIZE</b>	24 V, 18 AH Lithium-ion (1)	12 V, 18 AH (2)	12 V, 35 AH (2)	12 V, 40 AH (2)	12 V, 55 AH (2)	12 V, 55 AH (2)	12 V, 70 AH (2)	12 V, 50 AH (2)
<b>STANDARD BATTERY CHARGER</b>	2A, off-board, Lithium	2A, off-board	3.5A, off-board	5A, off-board	8A, off-board	5A, off-board	8A, off-board	5A, off-board
<b>PER-CHARGE RANGE<sup>9,5</sup></b>	Up to 15.4 km (9.6 miles)	Up to 14km (8.7 miles)	Up to 24.1 km (15 miles)	Up to 27 km (16.8 miles)	Up to 24.9 km (15.5 miles)	Up to 15.7 km (9.8 miles)	Up to 25.2 km (15.7 miles)	Up to 24.9 km (15.5 miles)
<b>BATTERY WEIGHT<sup>7</sup></b>	3.9 kg (8.81 lbs) each	14 kg (31 lbs) battery box	10.5 kg (23.3 lbs) each	14.1 kg (31.2 lbs) each	16.8 kg (37 lbs) each	16.8 kg (37 lbs) each	23.4 kg (51.6 lbs) each	16.8 kg (37 lbs) each
<b>WEIGHT OF HEAVIEST PIECE<sup>4</sup></b>	24.4 kg (54 lbs)	16.3 kg (36 lbs)	44.1 kg (97.4 lbs)	91.6 kg (202 lbs) <sup>8</sup>	62.3 kg (137.5 lbs)	44.9 kg (99 lbs)	88.4 kg (195 lbs)	47.6 kg (105 lbs)
<b>STANDARD SEAT WEIGHT</b>	N/A (seat is integrated with the base) (sling)	13.6 kg (30 lbs)	19.9 kg (44 lbs) (comfort, high-back)	23 kg (50.7 lbs) (high-back)	19.9 kg (44 lbs) (high-back)	23.5 kg (52 lbs) (high-back)	25.8 kg (57 lbs) (high-back)	N/A (seat is integrated with the base) (sling with power tilt)
<b>STANDARD SEAT SIZE</b>	41.9 cm x 44.4 cm (16.5" x 17.5")	43.1 cm x 45.7 cm (17" x 18")	45.7 cm x 45.7 cm (18" x 18")	40.6 cm x 45.7 cm (16" x 18") 45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 45.7 cm (20" x 18")	45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 45.7 cm (20" x 18")	45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 50.8 cm (20" x 20") 55.8 cm x 50.8 cm (22" x 20")	60.9 cm to 81.2 cm (24" to 32")	40.6 cm x 45.7 cm (16" x 18")
<b>COLOUR OPTIONS</b>	Pewter	Ruby Red, Pearl White	Ruby Red	Black Oynx, Pearl White, Pink Topaz, Garnet Red	Candy Apple Red	Jazzy Red, Jazzy Blue	Candy Apple Red, Viper Blue	Silver
	FOLDABLE	NEW GENERATION				JAZZY POWER CHAIRS		FUSION

<sup>1</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections. <sup>2</sup> Without front riggings. <sup>3</sup> Varies with user weight, terrain, battery condition and tire pressure. <sup>4</sup> Does not include seat or battery weights. <sup>5</sup> Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, - 5%. <sup>6</sup> Maximum weight capacity is reduced to 400 lbs. (181 kg) on 46 cm (18") deep seat configurations. <sup>7</sup> Battery weight may vary based on manufacturer. <sup>8</sup> Seat weight included (because tools are required to remove the seat). Battery weight not included. <sup>9</sup> Varies with user weight, terrain, battery type, battery condition and tire pressure. \*International configuration shown SEATING: A For Synergy<sup>®</sup> Seating. Contact your nearest Pride<sup>®</sup> stocklist for more information B Quantum<sup>®</sup> dealers only NOTE The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.