

TURNING VISION INTO REALITY

WHEN INNOVATION AND INSPIRATION COLLIDED THE SUPALITE WAS BORN

- One test drive of the SupaLite 4 is all you need to change your perception of a portable mobility scooter
- Engineered with you in mind!



SupaLite 4

Arm rests and basket are also included



Specification	SupaLite 4
Number of wheels	4
Color	Bronze Gold
Material	Aluminium
Front wheel size	175 x 50 mm (7 x 2")
Rear wheel size	200 x 65 mm (8 x 2.5")
Ground Clearance (Tiller)	60 mm (2.4")
Length	990 mm (39")
Width	570 mm (22.5")
Complete weight	21.1 kgs (46 lbs included battery & seat)
Weight without seat	14.3 kgs (31 lbs)
Weight of seat	5 kgs (11 lbs included seat frame)
Max Loading	120 kgs (264 lbs)
Turn Radius	930 mm (36.6")
Motor Output	260W
Transmission	Worm drive differential gearbox
Reverse	Forward/Reverse Switch
Brakes	Dynamic braking & Electromagnetic brake
Battery (Lithium)	24V11.6ah - 1.8kg (4 lbs)
Charger (Lithium battery)	Off board 24 volt 2 amp - 0.5 kg (1.1 lbs)
Max Speed	6.5 kph (4 mph) / 2nd speed choice - 3.8 kph (2.4 mph)
Slope grade ability	Max. recommended - 8 degrees
Travel Distance	Up to 10-13 km (6.2-8 miles)
Speed Reduction System	Reduces operating speed to a safe level when turning


Design concepts by Trek Mobility

Portable scooter specialists

ISO 13485 CE

Panasonic cell lithium battery made in Taiwan

UN 38.3 Certificate required for airline travel.
Download a copy at trekmobility.com.au



42 Achievement Way,
Wangara WA 6065
Ph: (08) 6500 3756
Fax: (08) 9302 2020
Email: admin@adhgroup.com.au

Specification subject to change without notice.

Made in Taiwan

PAT. PEND.