


Laserliner®

CableTracer Pro



Universal, flexible cable tracer set including transmitter and receiver

Rev.0211



– **Non-contact tracing of the transmission signal** by the receiver

– **Locates electrical cables, fuses, circuit breakers, metal pipes** (such as heating pipes) and much more

– **Locates interrupted cables** in existing installations and short-circuits in existing installation cables

– May be used with or without mains voltage

– **High transmission frequency** of 125 KHz allows for exact and fail-safe locating performance without power failures

– The receiver exactly locates the search object with the aid of a **bar diagram, numerical display and acoustic signals**

– Current setting shown on **clearly arranged, illuminated LC displays**


– Display of DC and AC voltages

– **Signal coding** allows as many as 7 senders to be used with one receiver and is thus ideal for complex installation settings

– **Integrated AC voltage detector** recognises and locates live lines

– **Permanent AC voltage warnings** increase safety with transmitter and receiver

– Integrated illumination of measuring points



Clearly arranged, illuminated LC display

Integrated illumination of measuring points

TECHNICAL DATA

TRANSMITTER CABLETRACER TX

Output signal: 125KHz
Nominal voltage: 12 – 250V
Measurement range: 12 – 400V AC/DC
Frequency range: 0 – 60Hz

SIGNAL CODES up to 7 different codes can be set

OVERVOLTAGE CATEGORY
CAT III 300V, pollution degree 2

POWER SUPPLY
1 x 9V block, IEC LR6, Alkali

DIMENSIONS (W x H x D)
68 x 130 x 32 mm

WEIGHT (incl. battery) 200 g

RECEIVER CABLETRACER REC V

Measurement ranges:
Voltage detection: 0 – 0,4 m measuring depth
Single-pole measurement: 0 – 2 m measuring d.
Two-pole measurement: 0 – 0,5 m measuring d.

POWER SUPPLY
1 x 9V block, IEC LR6, Alkali

DIMENSIONS (W x H x D)
59 x 192 x 37 mm

WEIGHT (incl. battery) 240 g



CableTracer Pro

including carrying case
+ transmitter TX
+ receiver REC V
+ connecting cable
+ test probes
+ test clamps
+ batteries

Packing dimension (W x H x D)
440 x 370 x 110 mm

ARTICLE	ARTICLE NO	EAN-CODE	PU
CableTracer Pro	083.070A	4 021563 671212	2