

Shipping Dimensions & Weight: 6.5" x 0.63" x 6.5" inches, 0.3lbs



PRODUCT FEATURES:

ETL listed

Dimmable

Cuttable every 1.66" inches where marked

High performance, low energy chips

50,000+ Hours of rated life

UV protected and fire retardant

PERFORMANCE:

Color	Model	Color Temp.	CRI	Lumen/ft.	Beam Angle	Power Consumption/ft.	Voltage	Current/ft.
Antique Warm White	LUM-COBP24-2200K	2,200K	> 95	330	180°	3.05W	24V	0.13A
Ultra Warm White	LUM-COBP24-2700K	2,700K	> 95	360	180°	3.05W	24V	0.13A
Warm White	LUM-COBP24-3000K	3,000K	> 95	365	180°	3.05W	24V	0.13A
Modern Warm White	LUM-COBP24-3500K	3,500K	> 95	370	180°	3.05W	24V	0.13A
Natural White	LUM-COBP24-4000K	4,000K	> 95	375	180°	3.05W	24V	0.13A
Cool White	LUM-COBP24-5500K	5,500K	> 95	390	180°	3.05W	24V	0.13A

USES:

- Cove, Soffit, Indirect Lighting
- Decorative Lighting
- Headboards & Mirrors
- Restaurants, Hotels, Theaters
- Staircase, Handrail, Step Lighting
- Bookshelves & Display Cases
- Gallery & Museum Lighting
- Wine Racks & Desks
- Back-lit Signs, Retail Spaces, Window Displays
- Accent & Mood Lighting

SPECIFICATIONS:

SKU:	LUM-COBP24
Available Colors:	2200K, 2700K, 3000K, 3500K, 4000K, & 5500K
IP Rating:	IP20 (Indoor Only)
Voltage:	24V DC
Power Output:	3.05 Watts/Ft.
Reel Length:	16.4 Ft.
Dimensions:	0.31" X 0.50" Inches (W X H)
CRI:	> 95
LED Diodes:	100/Ft.
LED Chips:	COB 922
Lumens:	330-390/Ft.
Operating Temp:	-68°F ~ 176°F



WIRE EXTENDER SERIES



End to End Clip (6 Pack)
LUM-WIRECT




End to End Clip (6 Pack)
LUM-WIREXT


CONNECTORS



End to End Clip
LUM-COB8BB-E2E



End to Loose Wire Connector
LUM-COB8BX-E2P



End to End Connector Wire Clip
LUM-COB8BX-CBC

POWER ADAPTER CABLE




Male Power Adapter Cable
LUM-MPP8ST21



Female Power Adapter Cable
LUM-FPP8ST21

18 GAUGE WIRE SPOOLS



18 Gauge Wire Spool
LUM-W18SC025ft | 50ft | 100ft

POWER SUPPLIES



Power Adapter
LUM-PA24XXW
36W | 60W | 96W |



Magnetic LED Transformer
LUM-PD24XXXD | 40W | 60W |
96W | 150W | 200W | 300W




Electronic LED Transformer
LUM-PD24XXWE
40W | 60W | 96W



Mean Well Driver
LUM-MWXXX24H 35W | 100W |
185W | 240W | 320W | 600W

CORNER CHANNEL WITH DIFFUSER




Aluminum Corner Channel
LUM-LP1919U-XX (4ft or 8ft)



Endcap Solid
LUM-LP1919U-ECN




Endcap with Hole
LUM-LP1919U-ECH



Channel Mounting Clip
LUM-LP1919U-CL

RECESSED CHANNELS WITH DIFFUSER



Aluminum Recessed Deep Channel
LUM-P2115B-XX (4ft or 8ft)
(Available in Silver or Black)




Endcap Solid
LUM-P2115B-ECN
(Available in White or Black)



Endcap with Hole
LUM-P2115B-ECH
(Available in White or Black)



Channel Mounting Clip
LUM-P2115B-CL




Aluminum Recessed Channel
LUM-P2206D-XX (4ft or 8ft)



Endcap Solid
LUM-P2206D-ECN




Endcap with Hole
LUM-P2206D-ECH



Channel Mounting Clip
LUM-P2206D-CL

SURFACE MOUNT CHANNEL WITH DIFFUSER



Aluminum Surface Mount Channel
LUM-P1707D-XX (4ft or 8ft)



Endcap with Hole
LUM-P1707D-ECH



Endcap Solid
LUM-P1707D-ECN




Channel Mounting Clip
LUM-P1707D-CL



Straight Channel Connector
LUM-P1707D-SC



90° Angle Channel Connector
LUM-P1707D-AC



Aluminum Surface Mount High Channel
LUM-P1715B-XX (4ft or 8ft)



Endcap with Hole
LUM-P1715B-ECH




Endcap Solid
LUM-P1715B-ECN




Channel Mounting Clip
LUM-P1715B-CL


COLOR OPTIONS:




Antique Warm White
2,200K




Ultra Warm White
2,700K




Warm White
3,000K



Modern Warm White
3,500K



Natural White
4,000K



Cool White
5,500K

Channel Type:	SKU:	Channel Profile:	End Caps:	Channel Mockup:
Aluminum Recessed Deep Channel	LUM-P2115B-XX (4ft or 8ft) <i>(Available in Silver or Black)</i>			
Aluminum Recessed Channel	LUM-P2206D-XX (4ft or 8ft)			
Aluminum Corner Channel	LUM-LP1919U-XX (4ft or 8ft)			
Aluminum Surface Mount Channel	LUM-P1707D-XX (4ft or 8ft)			
Aluminum Surface Mount High Channel	LUM-P1715B-XX (4ft or 8ft)			

INSTALLATION DIAGRAM: 24V LED STRIP LIGHT

