



MODEL: LUM-1FLD50













Lumilum LED Flood Light Series offers an excellent cost/value proposition in today's energy and lighting-design conscious environment. The products in this series are an efficient replacement option for fixtures that use metal halide and halogen bulbs, at a cost that pays for itself over a relatively short period of time.

PRODUCT FEATURES

- 50,000 hours of maintenance-free operation
- Uses up to 90% less energy when compared to the HID equivalent
- Color Temperature 6,000K
- CRI: >70
- Yoke-mounted head with 270° rotation capacity
- Universal voltage (120V-277V)
- Ideal for wet locations
- Suitable for ground mounting, up-lighting & down-lighting
- Insect-proof
- UL Listed *except RGB models
- RoHS compliant
- 3-year limited warranty

IDEAL USES

- Landscaping
- Exteriors
- Building facades
- Loading docks
- Signs and displays
- Walkways

TECHNICAL SPECIFICATIONS

	Model:	LUM-1FLD50
General Parameters	Power Consumption	152W
	Lumen Output	>14000 LM
	Lifespan	50,000 Hours
	Color Temp. (CCT)	6,000K
	CRI	>75
	Beam Angle	120°
	IP Rating	IP65 (Suitable for wet locations)
	LED Manufacturer	CREE
	Driver	Meanwell
	Warranty	3 Years
Physical Description	Housing	Aluminum
	Lens	Tempered Clear Glass
	Finish	Textured Architectural Powdercoat Paint
	Color	Standard: Dark Bronze; Special Order: Black, White, Gray
	Mounting	Yoke-mounted with 270° capacity

DIMENSIONS



