

INSTRUCTION TO COUNTER TOP FILTER CHANGE

1. Take a tea towel and spread it on your kitchen counter, beside the sink.
2. Take the water system and laydown, it is not necessary to detach diverter valve from faucet
3. Be sure to have the base on your LEFT, top of the system on your right
4. Wrap the wrench (given to you with the system) like a hook, and pull TOWARD YOU, just to loosen the housing, use your hands to do the rest.
5. Turn the system over to the sink, there will be some water into the housing, take the old filter and gasket out, rinse the housing.
6. Insert the filter into the housing with the opening facing toward to sealing (Open Housing)
7. Shake the filter around the housing a little to be sure that is sitting in the correct position
8. If the Filter has **ONE gasket**, the gasket **MUST FACE THE BASE**. If a filter has two gaskets, it does not matter which way goes into the housing.
9. Put the base onto the housing and screw it back on, UP SIDE DOWN
10. Repeat with all the other filters, the same way.

When done, be sure to run the water for 5-8 minutes. Enjoy pure refreshing water.

INSTRUCTION TO UNDER THE COUNTER FILTER CHANGE

*****TURN THE WATER OFF to the system, Turn the faucet on to release the pressure from the system.**

1. Take a towel and spread it on the floor near your kitchen sink.
2. Take the water system and laydown.
3. Be sure to have the BRACKET on your LEFT, top of the system on your right
4. Wrap the wrench (given to you with the system) like a hook, and pull TOWARD YOU, just to loosen the housing, use your hands to do the rest.
5. Over the sink, there will be some water into the housing, take the old filter and gasket out, rinse the housing
6. Insert the filter into the housing with the opening facing toward to sealing (Open Housing)
7. Shake the filter around the housing a little to be sure that is sitting in the correct position
8. **If the Filter has ONE gasket, the gasket MUST FACE THE BRACKET**. If a filter has two gaskets it does not matter which way goes into the housing.
9. Put the bracket onto the housing and screw it back on, UP SIDE DOWN,
10. Repeat with all the other filters, the same way.

Turn the water back on and check for any leaks

When done, be sure to run the water for 5-8 minutes. Enjoy pure refreshing water.