Page: 1 of 5

This revision issued: August, 2016

Section 1 - Identification of The Material and Supplier

Magnum Top Gear Pty Ltd

33 Sir Joseph Banks St

Botany, NSW 2019

Phone: 02 9734 7267
Fax: 02 9601 6515
Email: topgear@topgear.net.au

Chemical nature: Active ingredient is an organic peroxide.

Trade Name: Benzoyl Peroxide 50% Hardener

Other Names: Catalyst or Hardening Component

Product Use: Hardening component in polyester resin system.

Creation Date: October, 2005

This version issued: August, 2016 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA Australia.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: Class 5.2 (ORGANIC PEROXIDE TYPE E, SOLID)

UN Number: 3108





GHS Signal word: DANGER.

Self reactive substances and mixtures or Organic Peroxide Type E

Skin Sensitisation Category 1

Serious eye irritation Category 2/2A

HAZARD STATEMENT:

H242: Heating may cause a fire.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

PREVENTION

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P220: Keep or store away from combustible materials.

P234: Keep only in original container.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P337: If eye irritation persists: seek medical attention.

P353: Rinse skin or shower with water.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P370+P378: In case of fire, note the following. Coarse water spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

STORAGE

P410: Protect from sunlight.

P420: Store away from other materials.

P411+P235: Store at temperatures not exceeding 30°C. Keep cool.

DISPOSAL

P501: If product can not be recycled, consider controlled incineration, or contact a specialist waste disposal company (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Smooth pasty solid.

Odour: Mild odour.

SAFETY DATA SHEET

Issued by: Magnum Top Gear Pty Ltd Phone: 02 9734 7267

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Page: 2 of 5

This revision issued: August, 2016

Phone: 02 9734 7267

Major Health Hazards: eye irritant, possible skin sensitiser, possible risk of impaired fertility.

Section 3 - Composition/Information on Ingredients					
Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m ³)	
Benzoyl peroxide	94-36-0	60-80	5	not set	
Dimethyl phthalate	131-11-3	10-30	5	not set	
Talc	14807-96-6	<10	2.5	not set	

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Gently blot away excess liquid. Irritation is unlikely. However, if irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed.

Eye Contact: Quickly and gently wipe or blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as a C1 combustible product. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. The presence of this product in a fire is likely to intensify the fire due to its oxidising properties. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Preferred extinguishing media are carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires. Ensure that no spillage enters drains or water courses.

Fire Fighting: When fighting fires involving significant quantities of this product, wear a splash suit complete with self contained breathing apparatus.

Flash point:

Upper Flammability Limit:

No data.

Lower Flammability Limit:

No data.

Autoignition temperature:

No data.

No data.

No data.

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC, butyl rubber. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Under no circumstances should sawdust or other combustible material be used. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle

SAFETY DATA SHEET

Issued by: Magnum Top Gear Pty Ltd

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

This revision issued: August, 2016

containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute reducing agent. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination, especially from combustible, polymerisable or reducing materials. Make sure that the product does not come into contact with or substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m ³)
Benzoyl peroxide	5	not set
Dimethyl phthalate	5	not set
Talc	2.5	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. **Ventilation:** This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC, butyl rubber.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Smooth pasty solid.

Odour: Mild odour.

Boiling Point: Not available.

Freezing/Melting Point: No specific data. Liquid at normal temperatures. **Volatiles:** No specific data. Expected to be low at 100°C.

Vapour Pressure:No data.Vapour Density:No data.Specific Gravity:No data.

Water Solubility: No data. Believed to be insoluble.

pH: No data.Volatility: No data.Odour Threshold: No data.

SAFETY DATA SHEET

Issued by: Magnum Top Gear Pty Ltd Phone: 02 9734 7267

Page: 4 of 5

This revision issued: August, 2016

Evaporation Rate: No data.

Coeff Oil/water Distribution: No data
Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Keep isolated from combustible materials.

Incompatibilities: reducing agents, combustible materials, readily polymerised materials.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Benzoyl Peroxide is Classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient Risk Phrases

Benzoyl Peroxide Conc>=20%: Xi; R36; R43

• Organic peroxide - type B

- Eye irritation category 2
- Skin sensitisation category 1

Potential Health Effects

Inhalation

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product may be mildly irritating, but is unlikely to cause anything more than mild discomfort which should disappear once contact ceases.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP. **IARC:** Benzoyl Peroxide is Class 3 - unclassifiable as to carcinogenicity to humans.

Talc is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

SAFETY DATA SHEET

Issued by: Magnum Top Gear Pty Ltd Phone: 02 9734 7267

Product Name: Benzoyl Peroxide 50% Hardener Page: 5 of 5

This revision issued: August, 2016

Phone: 02 9734 7267

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by some means. If neither of these options is suitable in-house, consider a licensed waste treatment facility.

Section 14 - Transport Information

UN Number: 3108, ORGANIC PEROXIDE TYPE E, SOLID

Hazchem Code: 2W

Special Provisions: SP122, SP274

Dangerous Goods Class: Class 5.2, Organic peroxides.

Packaging Group: Ⅱ

Packaging Method: 3.8.5.2, OP1, OP8

Class 5.2 Organic Peroxides shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Toxic Gases), 3 (Flammable Liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 6 (Toxic Substances, where the Toxic Substance is a fire risk substance), 7 (Radioactive Substances), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods, where the substance is a fire risk substance), Fire risk substances other than Dangerous Goods. They may however be loaded in the same vehicle or packed in the same freight container with Classes 6 (Toxic Substances except where the substances are fire risk substances), 9 (Miscellaneous Dangerous Goods except where the goods are fire risk substances) Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: Benzoyl peroxide, is mentioned in the SUSMP.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition

AICS Australian Inventory of Chemical Substances
CAS Number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer
SWA Safe Work Australia, formerly ASCC and NOHSC

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous

Chemicals - Code of Practice" (December 2011) Copyright © Kilford & Kilford Pty Ltd, August, 2016.

http://www.kilford.com.au/ Phone (02)9251 4532

SAFETY DATA SHEET

Issued by: Magnum Top Gear Pty Ltd

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)