

WOMEN'S TENCATE TECASAFE® PLUS 580 TAPED 2T HI VIS CLOSED FRONT SHIRT WITH CONCEALED FRONT PLACKET

BLC8075T

Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Closed front concealed placket with button closure
- Two piece structured contrast collar
- Two way radio loop or gas monitor loop on both sides of shoulders
- Action back panel ventilation with two openings and underarm ventilation
- Twin chest pockets with plastic press snap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

Fabric

- TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm
- Tecasafe® Plus Open Mesh

Arc Thermal Protection Value

- ATPV 6.5

Personal Protective Equipment Category

- PPE 1


Size

- 8 - 24



Yellow/Navy
(TT01)

Orange/Navy
(TT02)



TENCATE
Tecasafe® Plus

BLC8075T

www.bisleyworkwear.com.au

TECHNICAL FAQ's

What is the front body length (shoulder neck point to hem)?

8: 73cm, **10:** 74cm, **12:** 75cm, **14:** 76cm,
16: 77cm, **18:** 78cm, **20:** 79cm,
22: 80cm, **24:** 81cm,

What is UPF rating of the fabric on this shirt?

- UPF 50+

SIMILAR PRODUCTS



BL8098T
WOMENS TENCATE TECASAFE®
PLUS TAPED 2T HI VIS LW FR
VENTED SHIRT LS



BL8082T
TENCATE TECASAFE® PLUS 700
WOMENS TAPED 2TONE HI VIS FR
VENTED SHIRT LS



BL8097T
WOMENS TENCATE TECASAFE®
PLUS 580 TAPED HI VIS LW FR
VENTED SHIRT LS

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard

AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.

AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- This garment has a sun protection rating of UPF 50+ all colours.

ENA NENS 09-2014: NATIONAL GUIDELINES FOR SELECTION, USE & MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT FOR ELECTRICAL HAZARDS

- Designed to meet under these guidelines

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 6.5 cal/cm² PPE 1
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

ALL STYLES

WOMENS

Size	8	10	12	14	16	18	20	22	24
To fit bust size (cm)	85	90	95	100	105	110	115	120	125
To fit natural waist size (cm)	65	70	75	80	85	90	95	100	105
To fit lower waist size (cm)	72	77	82	87	92	97	102	107	112
To fit hip size (cm)	92	97	102	107	112	117	122	127	132
In-leg length (cm)	80	80	82	82	84	84	86	86	86

BLC8075T

www.bisleyworkwear.com.au