

# 3M TAPED FR DENIM JEAN Flame Resistant

## **BP8091T**

#### Features

- Inherent flame resistant denim fabric
- STO-NOR 9801 Reflective taped 'Hoop' pattern around legs
- · Reinforced stitching at front and back rise
- 7 reinforced belt loops
- 2 angled side pockets
- Twin back hip patch pockets with pocket flap
- YKK branded zip front fly

#### **Fabric**

• 70% Manmade Inherent Fibre, 30% Cellulosic Fibre Denim, 400 gsm (11.8oz)

#### Size

Regular: 77-112Stout: 87-132





Extra wide belt loop at CB



Twin needle top stitching along inner leg side seam for reinforcement





Back yoke for shaping

Twin back hip welt pocket covered with flaps and plastic press stud closure

6mm twin needle top stitching along back and front rise for extra strength

FR retroreflective tape stitched all around leg in hoop pattern, finishing at side seam.

Double turn hem

















### **TECHNICAL FAQ's**

### What is the in leg length on Regular (crotch to finish hem)?

• 77: 80cm, 82: 82cm,

**87:** 84cm, **92:** 84cm, **97:** 85cm, **102:** 85cm, **107:** 86cm, **112:** 86cm

### What is the in leg length on Stout (crotch to finish hem)?

• **87:** 78cm, **92:** 80cm, **97:** 80cm,

**102:** 82cm, **107:** 82cm, **112:** 84cm, **117:** 84cm, **122:** 84cm, **127:** 84cm,

132: 84cm

### **SIMILAR PRODUCTS**



**BP8000**3M TAPED WESTEX ULTRASOFT®
FR WORK PANT



**BP8090** TENCATE TECASAFE PLUS® FR PANT



**BP8090T**TENCATE TECASAFE PLUS®
TAPED FR PANT

### **AUSTRALIAN & INTERNATIONAL STANDARDS**

#### Australian/ New Zealand Standards

- AS/NZS 2621:1998: Textiles Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
   BISLEY WORKWEAR GARMENTS USE THE CORRECT CARE LABELLING SUITED TO THEIR TYPE AND FABRICATION
- AS/NZS 1957:1998: Textiles Care Labelling
  BISLEY WORKWEAR GARMENTS ARE PROVIDED WITH CARE INSTRUCTIONS SUITED TO THEIR TYPE AND FABRICATION
- **AS/NZS 2622:1996:** Textile Products Fibre Content Labelling BISLEY WORKWEAR GARMENTS ACCURATELY LIST THE FABRIC FIBRE CONTENT
- AS/NZS 4399:1996: Sun Protective Clothing

   Evaluation and Classification

   THIS GARMENT HAS A SUN PROTECTION

   RATING OF UPF 50+ FOR ALL COLOURS

- AS/NZS 1020:1995: The Control of Undesirable Static Electricity

  THIS GARMENT IS 100% COTTON WITH NO METAL ZIPS OR BUTTONS, THEREFORE IT MAY BE USED AS A STATIC CONTROL GARMENT
- **AS/NZS 1906.4:2010:** Hi Visibility Material For Safety Garments. RETROREFLECTIVE TAPE ON THIS GARMENT ALSO MEETS THE HIGHER RETROREFLECTIVE PERFORMANCE REQUIRED.

#### International Standards

 ASTM D5489-07: Standard Guide for Care Symbols for Care Instructions on Textile Products
 BISLEY WORKWEAR GARMENTS COMPLY WITH USA STANDARDS FOR CARE LABEL

SYMBOLS AND CONTENT DESCRIPTIONS

- NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE
  - ASTM F 1959 / F1959M-14 according to ASTM F1506-10a. ATPV 10.0cal/cm<sup>2</sup>
- BS EN 61482-1-2:2007 LIVE WORKING. PROTECTIVE CLOTHING AGAINST THE THERMAL HAZARDS OF AN ELECTRIC ARC
- **ISO 11612:2008** PROTECTIVE CLOTHING AGAINST HEAT AND FLAME
- **ISO 11611:2007** PROTECTIVE CLOTHING FOR USE IN WELDING AND ALLIED PROCESSES

<b>PANTS</b>													MENS
Size REGULAR	77R	82R	87R	92R	97R	102R	107R	112R					
To fit waist size (cm)	77	82	87	92	97	102	107	112					
To fit waist size (inches)	30	32	34	36	38	40	42	44					
In-leg length (cm)	80	82	84	84	85	85	86	86					
Size STOUT			<i>87S</i>	<i>928</i>	<i>97</i> \$	102S	107S	112S	117S	122S	127S	132S	
To fit waist size (cm)			87	92	97	102	107	112	117	122	127	132	
To fit waist size (inches)			34	36	38	40	42	44	46	48	50	52	
In-leg length (cm)			78	80	80	82	82	84	84	84	84	84	