

TENCATE TECASAFE® PLUS 700 FR PANT WITH DOUBLE LAYER KNEE

BP8093

Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Front angled pockets with reinforced opening
- Single back patch pocket with plastic stud flap closure
- Wide belt loops
- Double layer knees for extra durability
- YKK branded zip front fly

Fabric

- TenCate Tecasafe® Plus 700A FR Modacrylic/Lyocell/Aramid 238gsm

Arc Thermal Protection Value

- ATPV 10

Personal Protective Equipment Category

- PPE 2

Size

- Reg: 77R-112R
- Stout: 87S-132S



Navy
(BPCT)



TENCATE
Tecasafe® Plus

BP8093

www.bisleyworkwear.com.au

TECHNICAL FAQ's

What is the inleg length on Regular (crotch to finish hem)?

- **77:** 80cm, **82:** 82cm, **87:** 82cm, **92:** 84cm, **97:** 84cm, **102:** 86cm, **107:** 86cm, **112:** 88cm

What is the inleg length on Stout (crotch to finish hem)?

- **87:** 78cm, **92:** 80cm, **97:** 80cm, **102:** 82cm, **107:** 82cm, **112:** 84cm, **117:** 84cm, **122:** 84cm, **127:** 84cm, **132:** 84cm

SIMILAR PRODUCTS



BP8093T
TENCATE TTECASAFE® PLUS
700 TAPED FR PANT WITH
DOUBLE LAYER KNEE



BP8090
TENCATE TECASAFE®
PLUS 700 FR PANT



BPC8092
TENCATE TECASAFE® PLUS 700
ENGINEERED FR VENTED
CARGO PANT

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 10.0 cal/cm² PPE 2
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

PANTS: Regular

MENS

To fit waist size (cm)	77	82	87	92	97	102	107	112
To fit waist size (inches)	30	32	34	36	38	40	42	44
Inner leg length (cm)	80	82	82	84	84	86	86	88

PANTS: Stout

MENS

To fit waist size (cm)	87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	52
Inner leg length (cm)	78	80	80	82	82	84	84	84	84	84

BP8093

www.bisleyworkwear.com.au