

TENCATE TECASAFE® PLUS 580 TAPED HI VIS LIGHTWEIGHT FR NON VENTED SHIRT LS

BS8197T

Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Two piece structured collar
- Two way radio loop or gas monitor loop on both shoulders
- Concealed press snap front closure
- Twin chest pockets with plastic press snap flap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

Fabric

- TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm

Arc Thermal Protection Value

- ATPV 6.5

Personal Protective Equipment Category

- PPE 1

Size

- S - 6XL



Orange
(BVE0)



FR Retroreflective tape stitched all around body and upper sleeves in hoop pattern



TENCATE
Tecasafe® Plus

BS8197T

www.bisleyworkwear.com.au

TECHNICAL FAQ's

What is the sleeve length (sleeve head to cuff)?

- S:** 60cm, **M:** 61.5cm, **L:** 63cm,
XL: 64.5cm, **2XL:** 66cm, **3XL:** 67.5cm,
4XL: 69cm, **5XL:** 70.5m, **6XL:** 72cm

What is UPF rating of the fabric on this shirt?

- UPF 50+

SIMILAR PRODUCTS



BS8238T

TENCATE TECASAFE® PLUS 480
 TAPED HI VIS LIGHTWEIGHT FR
 VENTED SHIRT LS



BS8097T

TENCATE TECASAFE® PLUS 580
 TAPED HI VIS FR
 VENTED SHIRT LS



BS8198T

TENCATE TECASAFE® PLUS 580
 TAPED 2T HI VIS LW FR
 NON VENTED SHIRT LS

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard

AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.

AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- This garment has a sun protection rating of UPF 50+ for Orange

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 6.5 cal/cm² PPE 1
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm² / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten, flaming debris. No after flame.

SHIRTS

MENS

| Size | S | M | L | XL | 2XL | 3XL | 4XL | 5XL | 6XL |
|----------------------------|-------|-------|-------|-------|-----|-----|-----|-----|-----|
| To fit neck size (cm) | 37/38 | 39/40 | 41/42 | 43/44 | 46 | 48 | 50 | 52 | 54 |
| To fit chest size (cm) | 92 | 97 | 102 | 107 | 112 | 117 | 122 | 127 | 132 |
| To fit chest size (inches) | 36 | 38 | 40 | 42 | 44 | 46 | 48 | 50 | 52 |

BS8197T

www.bisleyworkwear.com.au