

Product Name:	Bluelab Combo Meter Plus
Product Code:	METCOMPLUS
UPC Code:	9421024920975
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	Sold as singular unit
Packaging Information:	
Packaged Weight:	0.49 kg / 1.08 lb
Packaged Length:	180 mm / 7.086 in
Packaged Width:	110 mm / 4.33 in
Packaged Height:	83 mm / 3.267 in
Sales Description:	
<i>NOTE: this copy can be used in brochures, catalogues or online</i>	
pH, conductivity and temperature in one portable handheld meter.	
<p>An all-in-one, convenient portable solution for accurate measurement of pH, conductivity and temperature in nutrient solution. The battery-powered, lightweight unit can be used anywhere, anytime to measure critical parameters related to nutrient uptake in plants.</p> <p>The Bluelab Leap pH probe also allows fast and accurate pH measurements direct from the rootzone in a wide range of growing media including soil, rockwool, coco coir and potting mixes - no more pH slurries or extraction mixes. The detachable Bluelab Leap pH Probe has a toughened spear-tip for improved durability and is lightning fast in nutrient solution.</p> <p>Easy to read backlit screen for lowlight environments, and simple push button operation to view your chosen parameter.</p> <p>Team with the Bluelab Carry Case and Bluelab care and calibration solutions for optimal performance.</p> <p>Probe cable lengths: 2 meters / 6.5 ft</p> <p>Register your product here: http://bluelab.com/product-registration</p>	
Features:	
<ul style="list-style-type: none"> • pH, conductivity and temperature measured with corded probes • Detachable Bluelab Leap pH probe with double junction, toughened spear-tip for fast and accurate pH measurements direct from the rootzone and in nutrient solution • Robust electrical conductivity probe with integrated temperature sensor • Conductivity scale options: EC, CF, PPM500, PPM700, viewed at the touch of a button • Lightweight and portable • Easy to read backlit LCD display for lowlight environments • Simple two-point pH calibration with 30-day calibration indicator • Over-range and under-range indicators • Low battery indicator • Auto-off function • 2 x AAA alkaline batteries included 	
Product Guarantee:	
Five year free repair or replacement guarantee*.	
* Six months for Leap pH Probe.	

Product Image:

Product images available for Screen or Web use:

Bluelab-ComboMeterPlus-MR-WEB

Product images available for PRINT:
Note: these images are high resolution in CMYK.

- Bluelab-ComboMeterPlus-MR-CMYK

Technical Specifications:

Measurement Range:	0.0 – 14.0 pH, 0.0 – 9.9 EC, 99 CF 0 – 4950 ppm 500 (EC x 500) 0 – 6930 ppm 700 (EC x 700) 0 – 50°C / 32 – 122°F
Resolution:	0.1 pH, 0.1 EC, 1 CF 10 ppm 500, 10 ppm 700 1°C / 1°F
Accuracy at 25°C / 77°F:	± 0.1 pH, ± 0.1 EC, ± 1 CF, ± 50 ppm 500, ± 70 ppm 700 ± 1°C / ± 2°F
Automatic Temperature Compensation:	Yes - EC Probe
Operating Environment:	0 – 50°C / 32 – 122°F
Calibration:	Not required for conductivity. pH requires two point, pH 7.0 & pH 4.0 or pH 10.0 calibration
Power Source:	2 x AAA alkaline batteries
User Manual Languages Available:	English
Certifications:	CE and FCC