

Luxart PerfectSteam

STEAM GENERATOR WITH AUTO POWER FLUSH

The Luxart PerfectSteam Generator with integrated FastStart technology allows users to enjoy steam in a matter of seconds – not like the typical several minutes provided by other brands. Water is stored in the tank at just the right temperature before steam is created, allowing for swift delivery of constant steam at a constant rate without any annoying steam lags or bursts. The in shower steam control allows the user to set and monitor temperatures all from inside the shower enclosure. The unit also includes a stainless steel drain pan and exclusive Auto PowerFlush, an unparalleled pressurized inner-tank cleaning system, for lasting durability and performance. The generator can be installed up to 50 feet from the steam room for easy storage.



MODEL	INPUT VOLTAGE	KW RATING	AMPS	WIRE	BREAKER	PHASE	MAX. ROOM SIZE
LXA8	208-240VAC	8.0	37	8	40	1	140 CU.FT.
LXA10	208-240VAC	10.0	46	8	50	1	240 CU.FT.
LXA12	208-240VAC	11.0	55	6	60	1	395 CU.FT.



Control and Steamhead Available in Four Finishes



LXTTC-OSS-CP
Polished Chrome



LXTTC-OSS-ORB
Oil Rubbed Bronze



LXTTC-OSS-BN
Brushed Nickel



LXTTC-OSS-PN
Polished Nickel

STEAM GENERATOR SPECS

Dimensions

18 1/2" L x 8" W x 13" H

Weight

28 lbs.

Safety Valve

3/4" NPT

Water Inlet

3/8" NPT

Steam Outlet

1/2" NPT

Drain Pan

3/4" NPT

Installation Notes

Generator is factory sized based on cubic footage of shower space: L x W x H = Steam Room Cubic Feet

For every additional foot of ceiling height over 8', use the next larger generator. Ceiling height cannot exceed 10'. Always round up when calculating the total cubic feet.