


FTTH UMM ADSS

(remote and peripheral load-bearing elements – metal wire)

International standard:
IEC60794; Telecordia gr-20; EN 50173; ISO/IEC 11801;
ANSI/TIA - 588-C.3

- 1 – Suspension member – steel wire
- 2 – Strength member – two steel wires
- 3 – Singlemode optic fibers meet
- 4 – Outer sheath – LSZH



Material of protective coating : G.657 A1
 singlemode optical fibre in accordance with recommendation of ITU-T g. 657 A1

OPERATING CHARACTERISTICS:

Quantity of optical fibres, pcs.	2
Cable diameter, mm	5,2 x 2,0
Cable weight, kg/km	20
Maximum allowed tensile force (short-term load), kN	1,0
Minimum bending radius, mm	20 x cable diameter
Maximum allowed crushing force, N/mm	500
Operation temperature range, °C	-40°C - +60°C
Storage temperature range, °C	-20°C - +60°C
Installation temperature range, °C	- 10°C - +60°C

AREA OF APPLICATION

Drop cable is designed for last-one-mile in the FTTx network, enhancing the accessibility to the fiber and maximizes the installation workability

FEATURES

- 2 parallel peripheral strength members protecting the fibers ensure good performance of crush resistance: Simple structure, small weight and high practicability
- Easy jacket removal without special tools
- Easily splice, simplify the installation and maintenance
- Environmental protection – Low smoke, zero halogen and flame retardant sheath
- Self-support structure

SINGLEMODE OPTICAL FIBRE	
TYPE OF FIBER CHARACTERISTICS	Low-loss high performance fiber SM
Fiber used: Corning® SMF-28® Ultra fiber	ITU-T G. 657 A1
OPTICAL CHARACTERISTICS	
Wavelength attenuation	-
850 nm	-
1300 nm	-
1310 nm	≤ 0,32 dB/km
1550 nm	≤ 0,18 dB/km
Mode field diameter	8,6-9,5 μm (1310 nm)
Cutoff wavelength	1190-1330 nm
λ _c (OF – 2 m)	≤ 1260 nm
λ _{cc} (OF or OC – 22 m)	-
Chromatic dispersion	≤ 18 pc/(nm.km)
1285 – 1330 nm	-
1550 nm	-
1530 – 1565 nm	-
1525 – 1575 nm	≤ 22 pc/(nm.km)
1625 nm	-
Band width	-
λ = 850 nm	-
λ = 1300 nm	-
Wavelength range with zero variance value	1300 – 1324 nm
Maximum slope of dispersion curve at the point of its zero value	≤ 0,092 pc/(nm ² .km)
Polarization mode dispersion (PMD) 1550 nm	≤ 0,2 pc.km ^{1/2}
Numerical aperture (NA)	-
GEOMETRICAL CHARACTERISTICS	
Non-circularity of core	-
Core diameter	-
Cladding diameter	125 ± 0,7 μm
Cladding Non-circularity	≤ 1,0 %
Excentricity	-
- core / cladding	-
- mode field / cladding	≤ 0,5 μm
Coating diameter	245 ± 10 μm
MECHANICAL CHARACTERISTICS	
Strength test	≥ 1,0 % (0,69 hPa)
Radius of own bend	≥ 4,0 m
Macrobend losses:	
- radius of mandrel, mm	10 15
- number of coils, pc.	10 1
- Increase in attenuation, dB at wavelength	
1550 nm	0,25 0,75
1625 nm	1,0 1,5
ENVIRONMENTAL IMPACTS	
Dependence of attenuation in the temperature range (-60...+85) °C at wavelength	
850 nm	-
1300 nm	-
1310 nm	≤ 0,05 dB/km
1550 nm	≤ 0,05 dB/km