Foot Grounders



Applications: Any manufacturing or handling of ESD sensitive devices such as microelectronics, semicundutors, circuit boads, sensors, and hard drives.



Electrostat Foot Grounders

Heel Grounders and Toe Grounders are made of nonmarring, 3-layer, rubber material. The black outer layer is lightly textured and will not mar floors or footwear. The inner layer consist of conductive material. The final layer against the shoe is made of a smooth, grey dissipative material.

An adjustable hook and loop strap secures the grounder. The blue, conductive nylon ribbon provides constant body contact.

The grounder will dissipate a 5,000 volt charge to zero in 0.01 sec. Heel Grounders and Toe Grounders are available with or without a 1 meg ohm resistor. Conductive material meets NFPA-99 and DOD Handbook 263A standards.

Features and Benefits

Heel Grounders

- ▲ Adjustable Hook and Loop Strap
- ▲ Conductive Polyester Ribbon for Body Contact
- ▲ Grounder will Dissipate a 5,000 Volt Charge to 0 in 0.01 Seconds
- ▲ Grounder is Available with or without 1 Meg Ohm Resistor
- ▲ Conductive Material Meets NFPA-99 and DOD Handbook 263A Standards

Toe Grounders

- ▲ Adjustable Hook and Loop Strap
- ▲ Conductive Polyester Ribbon for Body Contact
- ▲ Grounder will Dissipate a 5,000 Volt Charge to 0 in 0.01 Seconds
- ▲ Grounder is Available with or without 1 Meg Ohm Resistor
- ▲ Conductive Material Meets NFPA-99 and DOD Handbook 263A Standards
- ▲ Designed for High Heel Shoes



Foot Grounders



Heel Grounder Product No. ESP0030

Description

Heel Grounder with 1meg ohm Resistor



Toe Grounder Product No. ES0040

Description

Toe Grounder With 1 Meg Ohm Resistor

Additional

Styles Include:

ESP1000-6AB-10 ESP1000-10AB-10 ESP1000-12AB-10 Wrist Straps, 10mm

Wrist Straps, 7mm

ESP1000-6AB-7 ESP1000-10AB-7 ESP1000-12AB-7

Wrist Straps, 4mm

ESP1000-6AB-4 ESP1000-10AB-4

ESP1000-12AB-4

Distributed By:

