



# MATERIAL SAFETY DATA SHEET

## STEP ONE ADHESIVE MATS

### Identification

Product Code: CRP0430

Product Description: The Adhesive Mat is a disposable, adhesive coated film used for the removal of particles in critical environmental areas.

### Physical and Chemical Properties

#### Components:

|          |  |
|----------|--|
| Film     | Polyethylene   |
| Adhesive | Ethyl Acetate<br>MEK<br>Ethylhexylacrylate<br>Buthylacrylate |

#### Physical Data:

|          |  |
|----------|--|
| Film     | Form: Sheets<br>Color: Blue, White, Grey<br>Specific Gravity: 0.92 |
| Adhesive | Type: Acrylic Adhesive<br>Solubility: Soluble in Acetone E.A.      |

### Stability and Reactivity

Polyethylene Sulfuric Acid, Hydrochloric Acid, Nitric Acid Will soften P.E. Film.

Adhesive Acetone, E.A. Tolunen, Benzene Will Dissolve the Adhesive.

### Potential Health Effects/First Aid Measures

Potential Health Effects: Adhesive Mats has been manufactured and used in industrial and as consumer products without any hazard effects on health. Adhesive Mats has been categorized as non-toxic.

Eye contact will produce a mechanical irritation.  
Skin contact should produce no skin irritation, swelling, or sensitization.

a division of ...



[www.tsmfg.com](http://www.tsmfg.com)

Voice: 888-460-4440 / 858-586-9922  
Fax: 888-966-5550 / 858-586-0055  
7077 Consolidated Way, Building G  
San Diego, CA 92121 USA



## MATERIAL SAFETY DATA SHEET

### STEP ONE ADHESIVE MATS (continued)

First Aid- Eye Contact: Mechanical irritation- remove particle.  
Seek medical help if irritation persists.

#### Other Precautions

Storage: Lay flat and Do Not bend or place on uneven floor. Keep away from heat, flames, chemicals, and solvents. Do not store longer than 6 Mo.

a division of ...



[www.tsmfg.com](http://www.tsmfg.com)

Voice: 888-460-4440 / 858-586-9922  
Fax: 888-966-5550 / 858-586-0055  
7077 Consolidated Way, Building G