## Goggles





### **Safety Goggles**

These Goggles are made of a soft vinyl frame with a polycarbonate lens. The flexible frame molds comfortably to the face for a secure fit. The scratch-resistant, polycarbonate lens is available in clear or green tint and anti-fog. The goggles allow room for most prescription glasses and the adjustable headband provides a custom fit for any wearer. Various vent configurations in the frame allow airflow for cooling. **ANSI approved. Z87.1 1989** 

Available in:

Indirect Vent
Direct Vent

**Applications:** Construction, machining, milling, industrial, laboratory and similar industries requiring eye protection from particulates and splash.

## Features and Benefits

- Strong Polycarbonate
- Anti-fog
- Scratch Resistant
- 99.9% UV Protective
- Optically Correct

- Lightweight
- Durable
- Versatile Fit

#### **ANSI Standards**

ANSI Standard Z87.1-1989 details strict requirements for impact and penetration resistance. Rigorous testing includes a high mass impact test and high velocity impact test for spectacles, goggles, face shields and welding helmets. All eye wear shown on this page meet the ANSI standard.



# Goggles





**Product No.** SAP0142-C SAP0142-G

**Description** Indirect Vent Indirect Vent

Frame Color Clear

Green

**Packaging** 1 dozen/pack, 10pack/case 1 dozen/pack, 10pack/case



 $\mathbf{Expo}^{\mathsf{TM}}$ **Product No.** 

SAP1000-C SAP1000-G

**Description** Direct Vent

Direct Vent

Frame Color Clear

Green

**Packaging** 1 dozen/pack, 10pack/case 1 dozen/pack, 10pack/case

Keep safety glasses within reach with Nylon Cords

Product No. SAP900

**Description** 

**Colors** Nylon Cords

Black, Blue, Green, Red

**Packaging** 1 dozen per bag



Additional **QVIS** Styles Include:

SAP0140 SAP4000 SAP4100 **Traditional** 

**Classics** 

SAP3000 SAP3100 SAP3200 SAP3300

**Sport** SAP2000

SAP2100 SAP2200

**Visitors** SAP0144 SAP0148 Distributed By:



U.S. Corporate Headquarters 7077 Consolidated Way San Diego, California 92121 v: 858-586-9922 f: 858-586-0055