


TECHNICAL DATA SHEET

STATIC DISSIPATIVE FINGER COTS (Black)



Finger Cots



Static Dissipative
(Black)

Vector is a division of ...



www.tsmfg.com

Voice: 888-460-4440
Domestic: (760) 598-5599

Fax: 888-966-5550
Domestic: (760)-598-2145

1445 Engineer St
Vista, Ca 9208

Product Code: ESP0200

Sizes Available: Small Medium Large Extra Large

Packing: 5 gross in static shield bag
20 bags or 100 gross per case

Carton Measurement: 0.04m³ each
Gross weight is between 12.3 kgs to 16.6 kgs per carton depending on the product size

Specifications

Material: 100% Biodegradable Natural Rubber

Dimension: Small Medium Large Extra Large

a) Length (mm): 62 to 72

b) Width (mm): 25 27 29 31

c) Thickness (mm): ← 0.08 to 0.13 →

d) Ave. Weight (g): 0.385 0.435 0.485 0.535

Physical Strength: Tensile Strength = Min. 200 kgs per cm²
Elongation at Break = Min. 600%

Cleanliness Test

a) NVR
-mg/g Max. 30

b) Water
Extractable Ions: F BR CL PO4 NO3 SO4 NA
-Interior & Exterior 0.05 0.05 3.5 0.05 2.5 2.5 2.5
-10 min. ambient
-ug per cm²

c) Particulate Count: Above 0.5 micron
-120 rpm 1 min. Max. 4,800
-no. per cm²

d) FTIR Silicone, amide, DOP absent

e) Copper Strip
Corrosion Test: No Discoloration

ESD Test

a) Surface Resistivity Average surface resistance of 10⁷ ohms per square surface unit

b) Static Decay Max. 1 second

c) Triboelectric Max. 20 volts

This is not a warranty that data provided on the products above are fit for a particular purpose. Total Source Manufacturing shall not be liable to anyone with respect to this information.