



GE  
Lighting

97594 - GE Ecolux® Blax® T4 - Facilities; Retail Display; Hospitality;  
Office; Restaurant; Warehouse

F13DBX/827/ECO4P

### Product Photo



### GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogram per mean lm hr	198.7
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	G24q-1
Bulb Shape	A17

### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	755 lm
Nominal Initial Lumen per Watt	69
Initial Lumens-nominal	900 lm
Color Rendering Index-CRI	82
Color Temperature	2700 K

### PRODUCT INFORMATION

Product Code	97594
Description	F13DBX/827/ECO4P
Alternative Unit Of Measure	PACK

### DIMENSIONS

Diameter	0.4 in
Nominal Length	5.0 in
Bulb Max Overall Length-MOL	5.0 in

### ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	60 W
Current Crest Factor (MAX)	5.25
Rated power (Watts)	13 W

### CAUTIONS & WARNINGS

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

Remove and install by grasping only plastic portion of the lamp.

### NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

