

97601 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality;

Office; Restaurant; Warehouse

F18DBX/841/ECO4P

Product Photo



GENERAL CHARACTERISTICS

Base Type Pin/Plug-In
Mercury Content 3 mg
Rated Life Hours-nominal 17000 h
Starting Temp (MIN) C-degrees 0 °C
Mercury-Picogrm per mean Im hr
Primary Application Facilities

Retail Display Hospitality Office Restaurant Warehouse

Product Technology Compact Fluorescent

Base G24q-2 Bulb Shape A19

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal970 lmNominal Initial Lumen per Watt69Initial Lumens-nominal1250 lmColor Rendering Index-CRI82Color Temperature4100 K

PRODUCT INFORMATION

Product Code 97601

Description F18DBX/841/ECO4P

Alternative Unit Of Measure PACK

DIMENSIONS

Base Face to Top of Lamp 5.2 in
Nominal Length 5.8 in
Bulb Max Overall Length-MOL 5.8 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts 65 W
Current Crest Factor (MAX) 5.25
Supply Current Freq nominal Hz 60 Hz
Rated power (Watts) 18 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

Aug 17, 2016 8:46:07 PM For additional information, visit www.gelighting.com