

97610 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

F26DBX/827/ECO4P

Product Photo



GENERAL CHARACTERISTICS

Base Type Pin/Plug-In
Mercury Content 3 mg
Rated Life Hours-nominal 17000 h
Starting Temp (MIN) C-degrees 0 °C
Mercury-Picogrm per mean Im hr
Primary Application Facilities
Retail Displ.

Retail Display
Hospitality
Office
Restaurant
Warehouse

Product Technology Compact Fluorescent

Base G24q-3 Bulb Shape G25

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal1530 lmNominal Initial Lumen per Watt69Initial Lumens-nominal1800 lmColor Rendering Index-CRI82Color Temperature2700 K

PRODUCT INFORMATION

Product Code 97610

Description F26DBX/827/ECO4P

Alternative Unit Of Measure PACK

DIMENSIONS

Base Face to Top of Lamp5.8 inNominal Length6.4 inBulb Max Overall Length-MOL6.4 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts 100 W
Current Crest Factor (MAX) 5.25
Supply Current Freq nominal Hz 60 Hz
Rated power (Watts) 26 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

