



GE  
Lighting

97613 - GE Ecolux® Blax® T4 - Facilities; Retail Display; Hospitality;  
Office; Restaurant; Warehouse

F26DBX/841/ECO4P

## Product Photo



### GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogram per mean lm hr	115.3
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	G24q-3
Bulb Shape	G25

### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	1530 lm
Nominal Initial Lumen per Watt	69
Initial Lumens-nominal	1800 lm
Color Rendering Index-CRI	82
Color Temperature	4100 K

### PRODUCT INFORMATION

Product Code	97613
Description	F26DBX/841/ECO4P
Alternative Unit Of Measure	PACK

### DIMENSIONS

Base Face to Top of Lamp	5.8 in
Nominal Length	6.4 in
Bulb Max Overall Length-MOL	6.4 in

### ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	100 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	26 W

### CAUTIONS & WARNINGS

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

### NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).