



GE  
Lighting

10032 - GE Cool White Starcoat® T5

F6T5/CW

## Product Photo



## GENERAL CHARACTERISTICS

Base Description	Miniature Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	6 mg
Mercury-Picogram per mean lm hr	5106.4
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	5000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G5
Bulb Shape	T5

## PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	235 lm
Nominal Initial Lumen per Watt	49
Initial Lumens-nominal	295 lm
Color Rendering Index-CRI	60
Color Temperature	4100 K

## PRODUCT INFORMATION

Product Code	10032
Description	F6T5/CW
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168100328
Standard Package GTIN	10043168100325
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168100328

## DIMENSIONS

Bulb Diameter (DIA) <Max>	0.63 in
Bulb Diameter (DIA) <Min>	0.53 in
Diameter	0.62 in
Face to End of Opposing Pin (B) <Max>	8.63 in
Face to End of Opposing Pin (B) <Min>	8.52 in
Nominal Length	9.0 in

## ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (rapid start) Min @ Temperature	130.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	6 W



## CAUTIONS & WARNINGS

### Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

### Warning

- Risk of Electric Shock
- Turn power off before inspection installation or removal.



Jun 12, 2017 3:29:07 PM For additional information, visit [www.gelighting.com](http://www.gelighting.com)