



GE
Lighting

**12723 - GE T2.25 (T2 1/4) - Low Voltage; Emergency Building;
Emergency Building Light**

774

GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Base Description	2-Pin
Filament	C-6
Bulb Material	Hard glass
Rated Life Hours-nominal	50 h
Atmosphere	Gas-filled
Primary Application	Emergency Building Low Voltage
Base	G4
Bulb Shape	T2.25 (T2 1/4)

PHOTOMETRIC CHARACTERISTICS

Mean Spherical Candlepower	13 cd
Nominal Initial Lumen per Watt	20
Initial Lumens-nominal	163 lm

PRODUCT INFORMATION

Product Code	12723
Description	774
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168127233
Standard Package GTIN	20043168127237
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168127233

DIMENSIONS

Diameter	0.28 in
Light Center Length (LCL)	0.77 in
Bulb Max Overall Length-MOL	1.0 in

ELECTRICAL CHARACTERISTICS

Input Voltage [nom]	12 V
Rated power (Watts)	8 W

CAUTIONS & WARNINGS

Caution

Risk of Burn

Allow lamp/fixture to cool before handling.

Warning

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Avoid direct water/liquid contact.

Dispose of lamp in a closed container.

Do not exceed rated voltage.

Do not turn on lamp until fully installed.


Do not use lamp if outer glass is scratched or broken.

Keep children away.

Use eye protection when handling

NOTES

.028" metal pins spaced 44mm (.157") apart. GE's two-pin lamps might not be compatible with all G-4 sockets since many sockets do not provide clearance for the exhaust tip.



Jun 13, 2017 7:32:55 PM For additional information, visit www.gelighting.com