



GE
Lighting

19901 - GE Compact HIR™ PAR30

50PAR30HIR/FL25

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium NP
Base Type	Pin/Plug-In
Filament	CC-8
Rated Life Hours-nominal	4000 h
Product Technology	Halogen
Bulb Shape	PAR30

PHOTOMETRIC CHARACTERISTICS

Beam Spread	25 deg
Center Beam Candle Pwr Candela	3200 cd
Nominal Initial Lumen per Watt	17
Initial Lumens-nominal	825 lm
Color Temperature	2810 K

PRODUCT INFORMATION

Product Code	19901
Description	50PAR30HIR/FL25
Alternative Unit Of Measure	EACH
Standard Package Quantity	15
Ean UPC	043168970471
Standard Package GTIN	00043168970471
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
Sales Unit	Each
UCC	043168199018
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168970471
Standard Package GTIN	00043168199018
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168199018

DIMENSIONS

Diameter	3.75 in
----------	---------

ELECTRICAL CHARACTERISTICS

Input Voltage [nom]	120 V
Rated power (Watts)	50 W

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Fire

- Keep combustible materials away from lamp.

Risk of Burn

- Allow lamp to cool before handling.

Risk of Electric Shock

- Turn power off before inspection installation or removal.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

- Do not use lamp if outer glass is scratched or broken.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.



Jun 14, 2017 9:07:58 PM For additional information, visit www.gelighting.com