



GE
Lighting

20832 - GE ConstantColor® Precise™ MR16

Q50MR16/C/WFL55

Product Photo



GENERAL CHARACTERISTICS

Base Description	2-Pin
Base Type	Pin/Plug-In
Filament	C-6
Rated Life Hours-nominal	6000 h
Product Technology	Halogen
Base	GX5.3
Bulb Shape	MR16

PHOTOMETRIC CHARACTERISTICS

Beam Spread	5 deg
Center Beam Candle Pwr Candela	900 cd
Initial Lumens-nominal	825 lm
Color Temperature	3050 K

PRODUCT INFORMATION

Product Code	20832
Description	Q50MR16/C/WFL55
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168991216
Standard Package GTIN	00043168991216
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	043168208321
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168991216
Standard Package GTIN	00043168208321
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168208321

DIMENSIONS

Diameter	2.0 in
----------	--------

ELECTRICAL CHARACTERISTICS

Input Voltage [nom]	12 V
Rated power (Watts)	50 W

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Fire

- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product-- see instructions.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

Risk of Burn

- Allow lamp/fixture to cool before handling.
- Turn power off before installing lamp.

Jul 7, 2017 8:54:43 PM For additional information, visit www.gelighting.com