

# 20867 - GE ConstantColor® Precise™ MR16

Q50MR16C/CG40 12

UV protection
Product Photo



## **GENERAL CHARACTERISTICS**

Base Description Base Type Filament Rated Life Hours-nominal Lamp Enclosure Type Product Technology Base Bulb Shape

### PHOTOMETRIC CHARACTERISTICS

Beam Spread Center Beam Candle Pwr Candela Color Temperature

# **PRODUCT INFORMATION**

Product Code Description Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC Alternative Unit Of Measure

2-Pin

C-6

6000 h

Halogen

GU5.3

**MR16** 

CASE

2.0 in

Pin/Plug-In

Covered glass

## DIMENSIONS

Diameter

### **ELECTRICAL CHARACTERISTICS**

Burn PositionUniversal burning positionInput Voltage [nom]12 VRated power (Watts)50 W

### **CAUTIONS & WARNINGS**

#### Caution

Lamp may shatter and cause injury if broken

Do not use lamp if outer glass is scratched or broken.

#### Warning

Risk of Burn

Allow lamp/fixture to cool before handling.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Do not use lamp if outer glass is scratched or broken.

#### Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Sep 20, 2016 9:52:23 PM For additional information, visit www.gelighting.com