

29604 - GE Quartzline® T5 - Stage & Studio; Double Ended; Overhead Projection BRH

# **Product Photo**



### **CAUTIONS & WARNINGS**

#### Caution

Risk of Burn

Allow lamp/fixture to cool before handling.

Turn power off before installing lamp.

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.

#### Warning

Risk of Electric Shock

Turn power off before inspection

installation or removal.

#### Risk of Fire

Keep combustible materials away from lamp.

Use in enclosed fixture rated for this product.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Avoid direct water

liquid or metal contact.

Do not exceed 110% of rated voltage.

### **GENERAL CHARACTERISTICS**

Base Description Base Type Filament Rated Life Hours-nominal Primary Application

Product Technology Base Bulb Shape

Initial Lumens-nominal

### PHOTOMETRIC CHARACTERISTICS

### Color Temperature

Nominal Initial Lumen per Watt

#### **PRODUCT INFORMATION**

Product Code Description Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC

## DIMENSIONS

Diameter Light Center Length

### **ELECTRICAL CHARACTERISTICS**

Burn Position Input Voltage [nom] Rated power (Watts) Recessed Single Contact Pin/Plug-In CC-8 60 h Stage & Studio Double Ended Overhead Projection Halogen R7s T5

30 30000 lm 3350 K

29604 BRH CASE

043168296045 10043168296042

Case 043168296045

0.62 in 0.75 in

> Universal burning position 120 V 1000 W

Do not use lamp if outer glass is scratched or broken.

Use in enclosed fixture rated for this product.

Jun 22, 2017 7:28:57 PM For additional information, visit www.gelighting.com