

44386 - GE T4 Q100CL/DC/2V **Product Photo**



GENERAL CHARACTERISTICS

| Base Description |
|--------------------------|
| Base Type |
| Bulb Finishes and Colors |
| Filament |
| Rated Life Hours-nominal |
| Product Technology |
| Base |
| Bulb Shape |

Double Contact Bayonet

Pin/Plug-In

Clear

CC-2V 750 h

Halogen

BA15d

Τ4

18

1800 lm

2950 K

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt Initial Lumens-nominal **Color Temperature**

PRODUCT INFORMATION

| Product Code | 44386 |
|----------------------------------|----------------|
| Description | Q100CL/DC/2V |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | |
| Ean UPC | 043168443869 |
| Standard Package GTIN | 10043168443866 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | |
| Sales Unit | Case |
| UCC | 043168443869 |
| | |

DIMENSIONS

| Diameter | 0.5 in |
|---------------------|---------|
| Light Center Length | 1.37 in |

ELECTRICAL CHARACTERISTICS

| Input Voltage [nom] | 120 V |
|---------------------|-------|
| Rated power (Watts) | 100 W |

CAUTIONS & WARNINGS

Caution

Risk of Burn

Allow lamp to cool before handling.

Turn power off before installing lamp.

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.

Warning

Lamp emits UV radiation which may cause eye/skin irritation.

Avoid exposure of eyes and skin to unshielded lamp.

Risk of Electric Shock

Turn power off before inspection

installation or removal.

Risk of Fire

Keep combustible materials away from lamp.

Use in enclosed fixture rated for this product.

Unexpected lamp rupture may cause injury, fire, or property damage

Use eye protection when handling lamp.

Use in enclosed fixture rated for this product.

Do not touch glass with bare hands.

Do not use lamp if outer glass is scratched or broken.

Do not exceed 110% of rated voltage.

Jun 28, 2017 7:25:20 PM For additional information, visit www.gelighting.com