

97599 - GE Ecolux® Biax® T4 - Facilities. Retail Display. Hospitality. Office. Restaurant. Warehouse F18DBX/830/ECO4P

Product Photo



GENERAL CHARACTERISTICS

Base Type Mercury Content Rated Life Hours-nominal Starting Temp (MIN) C-degrees Mercury-Picogrm per mean Im hr Primary Application Pin/Plug-In

3 mg

0 °C 181.9

17000 h

Facilities

Retail Display

Hospitality Office

Restaurant Warehouse

G24q-2

970 lm

Τ4

69 1250 lm

82

3000 K

97599

PACK

F18DBX/830/ECO4P

Compact Fluorescent

Product Technology Base Bulb Shape

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal Nominal Initial Lumen per Watt Initial Lumens-nominal Color Rendering Index-CRI Color Temperature

PRODUCT INFORMATION

Product Code Description Alternative Unit Of Measure

DIMENSIONS

Base Face to Top of Lamp	5.2 in
Nominal Length	5.8 in
Bulb Max Overall Length-MOL	5.8 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	65 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	18 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

Nov 17, 2016 9:45:32 PM For additional information, visit www.gelighting.com