

### 30157 - GE Quartzline® Showbiz® T5 - Stage & Studio

### DXW-Q1000T5/4CL 120

Figh color rendering (65-70CRI), much better than standard HPS

## **PRODUCT PHOTO**



### **CAUTIONS & WARNINGS**

#### Caution

#### Risk of Burn

Allow lamp/fixture to cool before handling.

Turn power off before installing lamp.

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.

### Warning

**Risk of Electric Shock** 

Turn power off before inspection

installation or removal.

#### Risk of Fire

Keep combustible materials away from lamp.

Use in enclosed fixture rated for this product.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Avoid direct water

## **GENERAL CHARACTERISTICS**

Base Description
Base Type
Filament
Rated Life Hours-nominal
Primary Application
Product Technology
Base
Bulb Shape

## PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt

# **PRODUCT INFORMATION**

Product Code Description Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC Alternative Unit Of Measure Standard Package Quantity Ean UPC Standard Package GTIN No Of Items Per Sales Unit No Of Items Per Standard Package Sales Unit UCC

DIMENSIONS

Diameter Light Center Length

## **ELECTRICAL CHARACTERISTICS**

Burn Position Input Voltage [nom] Universal burning position 120 V

**Recessed Single Contact** 

DXW-Q1000T5/4CL 120

Pin/Plug-In

Stage & Studio

CC-8

150 h

Halogen

R7s

Τ5

28

30157

CASE

043168301572

043168301572

043168301572

00043168301572

10043168301579

24

24

Case

EACH

1

1

Each

0.62 in

0.87 in

liquid or metal contact.

Do not exceed 110% of rated voltage.

Do not use lamp if outer glass is scratched or broken.

Use in enclosed fixture rated for this product.

Aug 29, 2019 9:32:46 PM | For additional information, visit products.currentbyge.com