

64258



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

| Product Number | 54262 | | | |
|-----------------------|--|--|--|--|
| Product Name | 64258 12V 40/CS 1/SKU | | | |
| Ordering Abbreviation | 64258 | | | |
| Brand Name | OSRAM | | | |
| Family Brand Name | XENOPHOT (HLX) | | | |
| General Description | 20 Watt, tunsgten halogen, low voltage without reflector | | | |
| Application | Projector | | | |
| Product Remark | - s (Operating Position) = Vertical, base down | | | |

Electrical data

| Nominal Wattage | 20 W |
|-----------------|------|
| Nominal Voltage | 12 V |
| Type of Current | AC |

Light technical data

| Luminous Flux | 350 lm |
|--------------------------------|----------|
| Light Center Length - LCL (in) | 0.768 in |
| Light Center Length - LCL (mm) | 19.5 mm |
| Color Temperature | 3050 K |
| Color Rendering Index | 100 |
| Average Rated Life | 2000 h |

Physical attributes


| Base | G4 Bipin |
|---------------------------------|-----------|
| Bulb Shape | Т9 |
| Maximum Overall Length (in) | 1.299 in |
| Maximum Overall Length (mm) | 33 mm |
| Length l (in) | 1.299 in |
| Length I (mm) | 33 mm |
| Diameter d (in) | 0.354 in |
| Diameter d (mm) | 9.00 mm |
| Distance a (in) | 0.768 in |
| Distance a (mm) | 19.5 mm |
| Filament Dimensions Length (in) | 0.0310 in |
| Filament Dimensions Length (mm) | 0.8 mm |

Product datasheet

| Filament Dimensions Width (in) | 0.138 in |
|--------------------------------|----------|
| Filament Dimensions Width (mm) | 3.5 mm |
| Reflector Coating | 9.00 |

Additional product data

| Operating Position | s90 |
|--------------------|---------|
| Class | C (gas) |



Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54262 | 4050300285153 | Folding box (SKU) | 1 | 1 in x 0.9 in x 2.8 in | |
| 54262 | 4050300891019 | Shipping box (Case) | 40 | 5.7 in x 4.2 in x 4.8 in | 0.4 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.