

G12 24IN/18GA/UL3239



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69370
Product Name	G1224IN18GAUL3239 84/CS 4/SKU
Ordering Abbreviation	G12 24IN/18GA/UL3239
Brand Name	OSRAM
General Description	G12 Socket 24" 3239/ 5kV
Old Part Number	F512019

Electrical data

Maximum Voltage (V)	600 V
Voltage - Pulse Rated (kV)	5 kV
Current (A)	4 A

Physical attributes

Length (in)	1.57 in
Length (mm)	40 mm
Width (in)	1.38 in
Width (mm)	35 mm
Height (in)	0.87 in
Height (mm)	22 mm
Body Material	Ceramic Steatite
Contact Material	Nickel Plated Copper
Wire Type	UL 3239
Wire Gauge (AWG)	18 AWG
Wire Color(s)	White
Lead Length (in)	24 in
Lead Length (mm)	610 mm
Lead Strip Length (in)	0.25 in
Lead Strip Length (mm)	6 mm

Additional product data

Lamp Base Reference	Med Bi-Pin
Maximum Operating Temperature (°C)	200 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	yes

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69370	4008321355942	Shipping box (Case)	4	4.9 in x 2.7 in x 3.3 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.