Product datasheet



EHA



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54585		
Product Name	EHA 120V 24/CS 1/SKU		
Ordering Abbreviation	ЕНА		
Brand Name	OSRAM 500 watt, tungsten halogen, medium to high voltage, single-ended		
General Description			
Application	Projector, Microfilm, Stage & Studio		
LIF Code	A1/254		
Product Remark	- Lamp has internal proximity reflector.		

Electrical data

Nominal Wattage	500 W	
Nominal Voltage	120 V	
Type of Current	AC	

Light technical data

Light Center Length - LCL (in)	1.424 in
Light Center Length - LCL (mm)	36.5 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	50 h

Physical attributes

Bulb Shape	Т6
Maximum Overall Length (in)	2.972 in
Maximum Overall Length (mm)	76.2 mm
Length I (in)	2.972 in
Length I (mm)	76.2 mm
Length I max. (in)	2.972 in
Length I max. (mm)	76.2 mm
Diameter d (in)	0.760 in
Diameter d (mm)	19.30 mm
Distance a (in)	1.424 in
Distance a (mm)	36.5 mm
Filament	C-13D

Product datasheet

Additional product data

Operating Position	s 90
Class	C (gas)
Method of Operation	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54585	4052899149830	Folding box (SKU)	1		
54585	4052899149847	Shipping box (Case)	24	8.3 in x 5.6 in x 4.5 in	1.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.