

# ENX-5



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

### Technical data

## **General product information**

Product Number	54913		
Product Name	ENX5 86V 24/CS 1/SKU		
Ordering Abbreviation	ENX-5		
Brand Name	OSRAM  360 watt, tungsten halogen, low to medium voltage with reflector		
General Description			
Application	Projector - Overhead		
Product Remark	- Lumens refers to screen lumens.		

#### **Electrical data**

Nominal Wattage	360 W
Nominal Voltage	86 V
Type of Current	AC

# Light technical data

Luminous Flux	540 lm
Working Distance a (in)	11.642 in
Working Distance a (mm)	298.5 mm
Color Rendering Index	100
Average Rated Life	75 h

## **Physical attributes**

Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length I (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	39.366 in
Diameter d (mm)	999.90 mm
Filament	CC-8
Reflector Coating	WHITE

## Additional product data

Operating Position	Any

### Product datasheet

Class	C (gas)
Method of Operation	MR16

### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54913	0046135549137	Folding box (SKU)	1		
54913	10046135549134	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.