



Halogen non-reflector

14623 95W G6.35 17V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data


General Information					
Cap-Base	G6.35 [G6.35]				
Philips Code	14623				
ANSI Code	-				
LIF Code	-				
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]				
Main Application	Projection				
Life to 50% Failures (Nom)	2000 h				
Light Technical					
Luminous Flux (Rated) (Nom)	2150 lm				
Correlated Color Temperature (Nom)	3050 K				
Color Rendering Index (Nom)	-				
Operating and Electrical					
Power (Rated) (Nom)	95 W				
Voltage (Nom)	17 V				

Mechanical and Housing					
Bulb Material	Quartz-UV Open				
Filament Shape	Flat				
Filament Dimensions WxH	5.24 x 3.13				
Luminaire Design Requirements					
Bulb Temperature (Max)	900 °C				
Pinch Temperature (Max)	350 °C				
Product Data					
Full product code	871150042667350				
Order product name	14623 95W G6.35 17V 1CT/10X10F				
EAN/UPC - Product	8711500426673				
Order code	924049819103				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	100				
Material Nr. (12NC)	924049819103				
Net Weight (Piece)	0.004 kg				

Datasheet, 2017, September 24 data subject to change

Halogen non-reflector

Dimensional drawing



14623 95W G6.35 17V

Product	D (max)	L (min)	L (max)	L	P (max)	Р	P (min)	C (max)
14623 95W	11.5 mm	31.5 mm	32.25	32	1.05 mm	1 mm	0.95 mm	50 mm
G6.35 17V			mm	mm				
1CT/10X10F								

